



***Az élelmiszer- és konzerv-
iparban alkalmazott láncok katalógusa***

Az Adix–Trade Kft. közel 30 éve forgalmaz láncokat, mint a láncok szakértője segít abban, hogy akár a gyártói ár töredékért jusson hozzá azokhoz a láncokhoz, alkalmazásokhoz, amely gépeikhez, berendezéseikhez, gyártósoruk működtetéséhez szükséges.

Termékkínálatunkat úgy alakítottuk ki, hogy vevőink számára széles termékválasztékot tudjunk biztosítani, különböző minőségi kategóriákban.


Cégünk komplex szolgáltatást kínál önnek. Nem csak terméket értékesítünk.

Meglévő lánc esetén vállaljuk a lánc felmérését, beazonosítását, megismerjük az üzemelési körülményeket és a vevői elvárásokat, aminek függvényében olyan megoldást ajánlunk, ami vevőink számára megbízható, folyamatos üzemelést biztosít.

Vállalunk standard láncok egyediesítését, valamint egyedi tervezésű láncok gyártását is.

Élelmiszeriparitermék-kínálatunkban megtalálhatók:



- görgősláncok
- rozsdamentes láncok
- conveyor láncok
- talpas láncok, láncvezetők



G Ö R G Ö S L Á N C O K

Roller chains links

Roller chains DIN 8187 European series




Simple roller chains / B Series

Reference	Pitch	Inner width	Roller diameter	Pin diameter	Pin length		Plate width	Plates thickness	Breaking load	Weight
DIN/ISO	P	B min	D1 max	D max	L max	Lc max	H max	T/T1 max	Q min	q
	mm	mm	mm	mm	mm	mm	mm	mm	KN	Kg/m
04B-1	6,000	2,80	4,00	1,85	6,80	7,8	5,00	0,60	3,0	0,11
05B-1	8,000	3,00	5,00	2,31	8,20	8,9	7,10	0,80	5,0	0,20
*06B-1	9,525	5,72	6,35	3,28	13,15	14,1	8,20	1,30	9,0	0,41
08B-1	12,700	7,75	8,51	4,45	16,70	18,2	11,80	1,60	18,0	0,69
10B-1	15,875	9,65	10,16	5,08	19,50	20,9	14,70	1,70	22,4	0,93
12B-1	19,050	11,68	12,07	5,72	22,50	24,2	16,00	1,85	29,0	1,15
16B-1	25,400	17,02	15,88	8,28	36,10	37,4	21,00	4,15/3,1	60,0	2,71
20B-1	31,750	19,56	19,05	10,19	41,30	45,0	26,40	4,5/3,5	85,0	3,70
24B-1	38,100	25,40	25,40	14,63	53,40	57,8	33,20	6,0/4,8	160,0	7,10
28B-1	44,450	30,99	27,94	15,90	65,10	69,5	36,70	7,5/6,0	200,0	8,50
32B-1	50,800	30,99	29,21	17,81	68,00	71,0	42,00	7,0/6,0	250,0	10,25
40B-1	63,500	38,10	39,37	22,89	82,20	89,2	52,96	8,5/8,0	355,0	16,35
48B-1	76,200	45,72	48,26	29,24	99,10	107,0	63,80	12/10	560,0	25,00
56B-1	88,900	53,34	53,98	34,32	114,80	123,00	77,80	13,5/12,0	850,0	35,78
64B-1	101,600	60,96	63,50	39,40	130,00	138,50	90,17	15,0/13,0	1,100,00	46,00
72B-1	114,300	68,58	72,39	44,48	147,40	156,40	103,60	17,0/15,0	1,400,00	60,80

* Straight plates

G Ö R G Ö S L Á N C O K

Roller chains DIN 8187 European series




Double roller chains / B Series

Reference	Pitch	Inner widthPi	Roller diameter	Pin diameter	Pin length		Plates width	Plates thickness	Transverse pitch	Breaking load	Weight per meter
DIN/ISO	P mm	B min mm	D1 max mm	D max mm	L max mm	Lc max mm	H max mm	T/T1 max mm	Pt mm	Q min kN	q Kg/m
05B-2	8,000	3,00	5,00	2,31	13,9	14,5	7,10	0,80	5,64	7,8	0,33
*06B-2	9,525	5,72	6,35	3,28	23,4	24,4	8,20	1,30	10,24	16,9	0,77
08B-2	12,700	7,75	8,51	4,45	31,2	32,2	11,80	1,60	13,92	32,0	1,34
10B-2	15,875	9,65	10,16	5,08	36,1	37,5	14,70	1,70	16,59	44,5	1,84
12B-2	19,050	11,68	12,07	5,72	42,0	43,6	16,00	1,85	19,46	57,8	2,31
16B-2	25,400	17,02	15,88	8,28	68,0	69,3	21,00	4,15/3,1	31,88	106,0	5,42
20B-2	31,750	19,56	19,05	10,19	77,8	81,5	26,40	4,5/3,5	36,45	170,0	7,20
24B-2	38,100	25,40	25,40	14,63	101,7	106,2	33,20	6,0/4,8	48,36	280,0	13,40
28B-2	44,450	30,99	27,94	16,90	124,6	129,1	36,70	7,5/6,0	59,56	360,0	16,60
32B-2	50,800	30,99	29,21	17,81	124,6	129,6	42,00	7,0/6,0	58,55	450,0	21,00
40B-2	63,500	38,10	39,37	22,89	154,5	161,5	52,96	8,5/8,0	72,29	630,0	32,00
48B-2	76,200	45,72	48,26	29,24	190,4	198,2	63,80	12/10	91,21	1000,0	50,00
56B-2	88,900	53,34	53,98	34,32	221,20	229,60	77,80	13,5/12,0	106,80	1,600,00	71,48
64B-2	101,600	60,96	63,50	39,40	249,90	258,40	90,17	15,0/13,0	119,89	2,000,00	91,00
72B-2	114,300	68,58	72,39	44,48	283,70	292,70	103,60	17,0/15,0	136,27	2,500,00	120,40

* Straight plates

Roller chains DIN 8187 European series




Triple roller Chains / B Series

Reference	Pitch	Inner width	Roller diameter	Pin diameter	Pin length		Plates width	Plates thickness	Transverse pitch	Breaking load	Weight per meter
DIN/ISO	P	B min	D1 max	D max	L max	Lc max	H max	T/T1 max	Pt	Q min	q
	mm	mm	mm	mm	mm	mm	mm	mm	mm	KN	Kg/m
05B-3	8,000	3,00	5,00	2,31	19,5	20,2	7,10	0,80	5,64	11,1	0,48
*06B-3	9,525	5,72	6,35	3,28	33,5	34,6	8,20	1,30	10,24	24,9	1,16
08B-3	12,700	7,75	8,51	4,45	45,1	46,1	11,80	1,60	13,92	47,5	2,03
10B-3	15,875	9,65	10,16	5,08	62,7	64,1	14,70	1,70	16,59	66,7	2,77
12B-3	19,050	11,68	12,07	5,72	61,5	63,1	16,00	1,85	19,46	86,7	3,46
16B-3	25,400	17,02	15,88	8,28	99,8	101,2	21,00	4,15/3,1	31,88	160,0	8,13
20B-3	31,750	19,56	19,06	10,19	114,2	117,9	26,40	4,5/3,5	36,45	250,0	10,82
24B-3	38,100	25,40	25,40	14,63	150,1	154,6	33,20	6,0/4,8	48,36	426,0	20,10
28B-3	44,450	30,99	27,94	15,90	184,2	188,7	36,70	7,5/6,0	59,56	530,0	24,92
32B-3	50,800	30,99	29,21	17,81	183,2	188,2	42,00	7,0/6,0	58,55	670,0	31,56
40B-3	63,500	38,10	39,37	22,89	226,8	233,8	52,96	8,5/8,0	72,29	950,0	48,10
48B-3	76,200	45,72	48,26	29,24	281,6	289,4	63,80	12/10	91,21	1500,0	75,00
56B-3	88,900	53,34	53,98	34,32	327,80	336,20	77,80	13,5/12,0	106,60	2,240,00	107,18
64B-3	101,600	60,96	63,50	39,40	369,80	378,30	90,17	15,0/13,0	119,89	3,000,00	136,00
72B-3	114,300	68,58	72,39	44,48	420,00	429,00	103,60	17,0/15,0	136,27	3,750,00	180,00

* Straight plates

G Ö R G Ö S L Á N C O K

Roller chains DIN 8188 American series




Simple roller chains / A Series

Reference		Pitch	Inner width	Roller diameter	Pin diameter	Pin length		Plates width	Plates thickness	Breaking load	Weight per meter
DIN/ISO	ASA	P mm	B min mm	D1 max mm	D max mm	L max mm	Lo max mm	H max mm	T max mm	Q min kN	q Kg/m
*04C-1	*25-1	6,350	3,18	3,30	2,31	7,90	8,40	6,00	0,80	3,20	0,15
*06C-1	*35-1	9,525	4,77	5,08	3,58	12,40	13,17	9,00	1,30	7,90	0,33
085-1	41-1	12,700	6,25	7,77	3,58	13,75	15,00	9,91	1,30	6,67	0,41
08A-1	40-1	12,700	7,85	7,95	3,96	16,60	17,80	12,00	1,50	14,10	0,62
10A-1	50-1	15,875	9,40	10,16	5,08	20,70	22,20	15,09	2,03	22,20	1,02
12A-1	60-1	19,050	12,57	11,91	5,94	25,90	27,70	18,00	2,42	31,80	1,50
16A-1	80-1	25,400	15,75	15,88	7,92	32,70	35,00	24,00	3,25	56,70	2,60
20A-1	100-1	31,750	18,90	19,05	9,53	40,40	44,70	30,00	4,00	88,50	3,91
24A-1	120-1	38,100	25,22	22,23	11,10	50,30	54,30	35,70	4,80	127,00	5,62
28A-1	140-1	44,450	25,22	25,40	12,70	54,40	59,00	41,00	5,60	172,40	7,50
32A-1	160-1	50,800	31,55	28,58	14,27	64,80	69,60	47,80	6,40	226,80	10,10
40A-1	200-1	63,500	37,85	39,68	19,85	80,30	87,20	60,00	8,00	353,80	16,15
48A-1	240-1	76,200	47,35	47,63	23,81	95,50	103,00	72,39	9,50	510,30	23,20

* Bush chains

Roller chains DIN 8188 American series




Double roller chains / A series

Reference	Pitch	Inner width	Roller diameter	Pin diameter	Pin length	Plates width	Plates thickness	Transverse Pitch	Breaking load	Weight per meter		
DIN/ISO	ASA	P mm	B min mm	D1 max mm	D max mm	L max mm	Lo max mm	H max mm	T max mm	Pt mm	Q min KN	q Kg/m
*04C-2	*25-2	6,350	3,18	3,30	2,31	14,50	15,00	6,00	0,80	6,40	7,00	0,28
*06C-2	*35-2	9,525	4,77	5,08	3,58	22,50	23,30	9,00	1,30	10,13	15,80	0,63
085-2	41-2	12,700	6,25	7,77	3,58	25,70	26,90	9,91	1,30	11,95	13,34	0,81
08A-2	40-2	12,700	7,85	7,95	3,96	31,00	32,20	12,00	1,50	14,38	28,20	1,12
10A-2	50-2	15,875	9,40	10,16	5,08	38,90	40,40	15,09	2,03	18,11	44,40	2,00
12A-2	60-2	19,050	12,57	11,91	5,94	48,80	50,50	18,00	2,42	22,78	63,60	2,92
16A-2	80-2	25,400	15,75	15,88	7,92	62,70	64,30	24,00	3,25	29,29	113,40	5,15
20A-2	100-2	31,750	18,90	19,05	9,53	76,40	80,50	30,00	4,00	35,76	177,00	7,80
24A-2	120-2	38,100	25,22	22,23	11,10	95,80	99,70	35,70	4,80	45,44	254,00	11,70
28A-2	140-2	44,450	25,22	25,40	12,70	103,30	107,90	41,00	5,60	48,87	344,80	15,14
32A-2	160-2	50,800	31,55	28,58	14,27	123,30	128,10	47,80	6,40	58,55	453,60	20,14
40A-2	200-2	63,500	37,85	39,68	19,85	151,90	158,80	60,00	8,00	71,55	707,60	32,24
48A-2	240-2	76,200	47,35	47,63	23,81	183,40	190,80	72,39	9,50	87,83	1.020,60	45,23

* Bush chains

G Ö R G Ö S L Á N C O K

Roller chains DIN 8188 American series




Triple roller chains / A series

Reference	Pitch	Inner width	Roller diameter	Pin diameter	Pin length	Plates width	Plates thickness	Transverse Pitch	Breaking load	Weight per meter		
DIN/ISO	ASA	P mm	B min mm	D1 max mm	D max mm	L max mm	Lc max mm	H max mm	T max mm	Pt mm	Q min KN	q Kg/m
*04C-3	*25-3	6,350	3,18	3,30	2,31	21,00	21,50	6,00	0,80	6,40	10,50	0,44
*06C-3	*35-3	9,525	4,77	5,08	3,58	32,70	33,50	9,00	1,30	10,13	23,70	1,06
08A-3	40-3	12,700	7,85	7,95	3,96	45,40	46,60	12,00	1,50	14,38	42,30	1,90
10A-3	50-3	15,875	9,40	10,16	5,08	57,00	58,50	15,09	2,03	18,11	66,60	3,09
12A-3	60-3	19,050	12,57	11,91	5,94	71,50	73,30	18,00	2,42	22,78	95,40	4,54
16A-3	80-3	25,400	15,75	15,88	7,92	91,70	93,60	24,00	3,25	29,29	170,10	7,89
20A-3	100-3	31,750	18,90	19,05	9,53	112,20	116,30	30,00	4,00	35,76	265,50	11,77
24A-3	120-3	38,100	25,22	22,23	11,10	141,40	145,20	35,70	4,80	45,44	381,00	17,53
28A-3	140-3	44,450	25,22	25,40	12,70	162,20	166,60	41,00	5,60	48,87	517,20	22,20
32A-3	160-3	50,800	31,55	28,58	14,27	181,80	186,60	47,80	6,40	58,55	680,40	30,02
40A-3	200-3	63,500	37,85	39,68	19,85	223,50	230,40	60,00	8,00	71,55	1.061,40	49,03
48A-3	240-3	76,200	47,35	47,63	23,81	271,30	278,60	72,39	9,50	87,83	1.530,90	71,60

* Bush chains




Roller chains with straight plates



Reference	Pitch	Inner width	Roller diameter	Pin diameter	Pin length		Plates width	Plates thickness	Transverse pitch	Breaking load	Weight per meter
DIN/ISO	P	B min	D1 max	D max	L max	Lc max	H max	T/T1 max	Pt	Q min	q
	mm	mm	mm	mm	mm	mm	mm	mm	mm	KN	Kg/m
C08B-1	12,700	7,75	8,51	4,45	16,7	18,2	11,8	1,60	-	18,0	0,80
C10B-1	15,875	9,85	10,16	5,08	19,5	20,9	14,7	1,70	-	22,4	1,06
C12B-1	19,050	11,68	12,07	5,72	22,5	25,2	16,0	1,85	-	29,0	1,32
C16B-1	25,400	17,02	15,88	8,28	36,1	39,1	21,0/24,0	4,15/3,1	-	60,0	3,08/3,49
C20B-1	31,750	19,56	19,05	10,19	41,3	45,0	26,4	4,5/3,5	-	95,0	4,16
C24B-1	38,100	25,40	25,40	14,63	53,4	57,8	33,2	6,0/4,8	-	160,0	7,47
C28B-1	44,450	30,99	27,94	15,90	65,1	69,5	36,7	7,5/6,0	-	200,0	9,90
C32B-1	50,800	30,99	29,21	17,81	66,0	71,0	42,0	7,0/6,0	-	250,0	10,45
C08B-2	12,700	7,75	8,51	4,45	31,2	32,2	11,8	1,60	13,92	32,0	1,45
C10B-2	15,875	9,85	10,16	5,08	36,1	37,5	14,7	1,70	16,59	44,5	2,00
C12B-2	19,050	11,68	12,07	5,72	42,0	44,7	16,0	1,85	19,46	57,8	2,62
C16B-2	25,400	17,02	15,88	8,28	68,0	71,0	21,0/24,0	4,15/3,1	31,88	106,0	6,10/6,92
C20B-2	31,750	19,56	19,05	10,19	77,8	81,5	26,4	4,5/3,5	36,45	170,0	8,23
C24B-2	38,100	25,40	25,40	14,63	101,7	106,2	33,2	6,0/4,8	48,36	280,0	14,77
C28B-2	44,450	30,99	27,94	15,90	124,6	129,1	36,7	7,5/6,0	59,56	360,0	19,82
C32B-2	50,800	30,99	29,21	17,81	124,6	129,6	42,0	7,0/6,0	58,55	450,0	20,94
C08B-3	12,700	7,75	8,51	4,45	45,1	46,1	11,8	1,60	13,92	47,5	2,10
C10B-3	15,875	9,85	10,16	5,08	52,7	54,1	14,7	1,70	16,59	66,7	2,87
C12B-3	19,050	11,68	12,07	5,72	61,5	64,2	16,0	1,85	19,46	86,7	3,89
C16B-3	25,400	17,02	15,88	8,28	99,8	102,9	21,0/24,0	4,15/3,1	31,88	160,0	9,12/10,34
C20B-3	31,750	19,56	19,05	10,19	114,2	117,9	26,4	4,5/3,5	36,45	250,0	11,34
C24B-3	38,100	25,40	25,40	14,63	150,1	154,6	33,2	6,0/4,8	48,36	425,0	22,10
C28B-3	44,450	30,99	27,94	15,90	184,2	188,7	36,7	7,5/6,0	59,56	530,0	29,64
C32B-3	50,800	30,99	29,21	17,81	183,2	188,2	42,0	7,0/6,0	58,55	670,0	31,27

G Ö R G Ö S L Á N C O K

Side bow roller chains American / european series




Reference	Pitch	Inner width	Roller diameter	Pin diameter	Pin length	Plates width	Plates thickness	Side bow radius	Breaking load	Weight per meter
DIN/ISO	P	B min	D1 max	D max	L max	Lc max	H max	T/T1 max	R min	Q min
	mm	mm	mm	mm	mm	mm	mm	mm	mm	kN
40SB	12,700	7,85	7,95	3,96	16,90	18,10	11,70	1,50	350,00	13,80
50SB	15,875	9,40	10,16	4,37	20,70	22,70	14,90	2,03	400,00	20,60
60SB	19,050	12,57	11,91	5,34	26,60	28,40	18,00	2,42	500,00	15,70
80SB	25,400	15,75	15,88	7,19	34,00	37,30	24,00	3,25	715,00	40,90
08BSB	12,700	7,75	8,51	3,97	17,40	18,70	11,80	1,60	400,00	14,00
10BSB	15,875	9,65	10,16	4,50	20,10	21,50	14,70	1,70	400,00	16,60
12BSB	19,050	11,68	12,07	5,12	23,10	24,80	16,00	1,85	500,00	20,50
16BSB	25,400	17,02	15,88	7,90	36,50	39,70	21,00	3,7/3,0	500,00	55,60

Roller chains with attachments




Attachment 90° 1 side 1 hole

A-1



Attachment 90° 2 sides 1 hole

K-1



Roller chains with attachments standard ISO / B series

Reference	P	G	F	W	T1	H4	D4
DIN/ISO	mm	mm	mm	mm	mm	mm	mm
*06B	9,525	8,0	19,04	27,0	1,30	6,50	3,5
08B	12,700	9,5	25,40	36,4	1,60	8,90	4,5
10B	15,875	14,3	31,75	44,6	1,70	10,31	5,3
12B	19,050	16,0	38,10	52,4	1,85	13,46	6,4
16B	25,400	19,1	50,80	72,6	3,10	16,88	8,4
20B	31,750	35,0	63,50	100,5	3,50	19,80	9,0
24B	38,100	36,0	76,20	108,4	4,80	26,67	10,5

* Straight plates

Also available in stainless steel

Roller chains with attachments special / B series

Reference	P	G	F	W	T1	H4	D4
DIN/ISO	mm	mm	mm	mm	mm	mm	mm
*06B	9,525	8	19,0	27,0	1,30	6,5	3,5
08B	12,700	11	27,6	36,4	1,60	8,75	4,3
10B	15,875	14	31,6	45,6	1,70	10,5	5,3
12B	19,050	18	35,4	54,8	1,85	11,6	6,4
16B	25,400	24	53,8	77,6	3,10	16,3	8,2
20B	31,750	25	63,0	99	3,50	19,84	9
24B	38,100	30	76,2	118	4,80	26,7	11

* Straight plates

Also available in stainless steel

For other measures, please consult



G Ö R G Ö S L Á N C O K

Roller chains with attachments



Straight attachment 1 side 1 hole
SA-1

Straight attachment 2 sides 1 hole
SK-1



Roller chains with attachments standard ISO / B series

Reference	P	G	H2	H3	T1	D4
DIN/ISO	mm	mm	mm	mm	mm	mm
*06B	9,525	8,0	9,52	13,50	1,30	3,5
08B	12,700	9,5	13,35	18,90	1,60	4,3
10B	15,875	14,3	16,50	22,95	1,70	5,3
12B	19,050	16,0	21,45	28,60	1,85	6,4
16B	25,400	19,1	23,15	34,00	3,10	8,4
20B	31,750	35,0	30,60	45,70	3,50	9,0
24B	38,100	36,0	42,70	61,50	4,80	10,5

* Straight plates
Also available in stainless steel

Roller chains with attachments special / B series

Reference	P	G	H2	H3	T1	D4
DIN/ISO	mm	mm	mm	mm	mm	mm
*06B	9,525	8	9,5	13,5	1,30	3,5
08B	12,700	11	14,1	19,5	1,60	4,3
10B	15,875	14	16,2	23,2	1,70	5,3
12B	19,050	18	18,2	28,1	1,85	6,4
16B	25,400	24	25,4	37,35	3,10	8,2
20B	31,750	25	31,75	50	3,50	9
24B	38,100	30	36,51	55	4,80	11



* Straight plates
Also available in stainless steel
For other measures, please consult

Roller chains with attachments



Attachment 90° 1 side 2 holes
WA-2

Attachment 90° 2 sides 2 holes
WK-2



Roller chains with attachments standard ISO / B series

Reference	P	G	P1	F	W	T1	H4	D4
DIN/ISO	mm	mm	mm	mm	mm	mm	mm	mm
*06B	9,525	17,85	9,525	19,05	27,50	1,30	6,50	3,5
08B	12,700	24,00	12,700	25,40	36,4	1,60	8,90	4,3
10B	15,875	29,58	15,875	31,80	44,6	1,70	10,31	5,3
12B	19,050	34,05	19,050	38,10	52,4	1,85	13,46	6,4
16B	25,400	46,40	25,400	50,80	72,6	3,10	15,88	8,4
20B	31,750	58,10	31,750	63,00	100,5	3,50	19,80	9,0
24B	38,100	71,30	38,100	76,20	108,4	4,80	26,67	10,5

* Straight plates
Also available in stainless steel

Roller chains with attachments special / B series

Reference	P	G	P1	F	W	T1	H4	D4
DIN/ISO	mm	mm	mm	mm	mm	mm	mm	mm
*06B	9,525	17,75	9,525	19,0	27,0	1,30	6,5	3,5
08B	12,700	24,2	12,7	27,6	38,4	1,60	8,75	4,3
10B	15,875	29,9	15,875	31,6	45,6	1,70	10,5	5,3
12B	19,050	35,25	19,05	35,4	54,8	1,85	11,6	6,4
16B	25,400	45	25,4	53,8	77,6	3,10	16,3	8,2
20B	31,750	58	31,75	63,0	99	3,50	19,84	9
24B	38,100	72	38,1	76,2	118	4,80	26,7	11

* Straight plates
Also available in stainless steel
For other measures, please consult

G Ö R G Ö S L Á N C O K



Roller chains with attachments



Straight attachment 1 side 2 holes
WSA-2



Straight attachment 2 sides 2 holes
WSK-2



Roller chains with attachments standard ISO / B series

Reference	P	G	P1	H2	H3	T1	D4
DIN/ISO	mm	mm	mm	mm	mm	mm	mm
*06B	9,525	17,65	9,525	9,52	13,50	1,30	3,5
08B	12,700	23,30	12,700	13,35	18,90	1,80	4,3
10B	15,875	29,58	15,875	16,50	22,95	1,70	5,3
12B	19,050	34,05	19,050	21,45	28,60	1,85	6,4
16B	25,400	46,40	25,400	23,15	34,00	3,10	6,4
20B	31,750	58,10	31,750	30,50	45,70	3,50	9,0
24B	38,100	71,30	38,100	42,70	61,50	4,80	10,5

* Straight plates
Also available in stainless steel

Roller chains with attachments special / B series

Reference	P	G	P1	H2	H3	T1	D4
DIN/ISO	mm	mm	mm	mm	mm	mm	mm
*06B	9,525	17,75	9,525	9,5	13,5	1,30	3,5
08B	12,700	24,2	12,700	14,1	19,5	1,60	4,3
10B	15,875	29,9	15,875	16,2	23,2	1,70	5,3
12B	19,050	35,25	19,050	18,2	28,1	1,85	6,4
16B	25,400	45	25,400	25,4	37,35	3,10	8,2
20B	31,750	58	31,750	31,75	50	3,50	9
24B	38,100	72	38,100	38,51	55	4,80	11

* Straight plates
Also available in stainless steel





For other measures, please consult

Roller chains with extended pins



Every 2 Pitches

Every Pitches





Reference	P	B	D	L1	L	Lc
DIN/ISO	mm	mm	mm	mm	mm	mm
*06B	9,525	5,72	3,28	11,3	23,4	24,4
08B	12,700	7,75	4,45	15,5	31,2	32,2
10B	15,875	9,65	5,08	17,8	36,1	37,5
12B	19,050	11,68	5,72	20,7	42,0	43,6
16B	25,400	17,02	8,28	33,2	68,0	69,3

* Straight plates
Also available in stainless steel

For other measures, please consult


G Ö R G Ö S L Á N C O K

Roller chains with rubber blocks



Reference	Pitch	Inner width	Roller diameter	Pin dimensions		Plate and rubber blocks dimensions					Breaking load	Weight per meter
DIN/ISO	P	B min	D1 max	D max	L max	H max	A	C	H5	T2	Q min	q
	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	KN	Kg/m
08B-G1	12,70	7,75	8,51	4,45	20,0	11,8	14,6	24,2	12,3	1,60	18,0	1,19
08B-G2	12,70	7,75	8,51	4,45	34,3	11,8	28,4	24,2	12,3	1,50	32,0	2,07
10B-G1	15,875	9,65	10,16	5,08	23,2	14,7	16,8	30,0	17,0	1,70	22,4	1,62
10B-G2	15,875	9,65	10,16	5,08	39,7	14,7	33,3	30,0	17,0	1,70	44,5	2,56
12B-G1	19,05	11,68	12,07	5,72	25,7	16,0	19,6	36,0	21,0	1,85	29,0	2,01
12B-G2	19,05	11,68	12,07	5,72	45,3	16,0	39,1	36,0	16,0	1,85	57,8	3,21
16B-G1	25,40	17,02	15,88	8,28	39,7	21,0	29,1	49,0	21,4	1,60	58,0	3,83
16B-G2	25,40	17,02	15,88	8,28	71,68	21,0	61,0	49,0	21,4	1,60	116,0	7,32
16A-G1	25,40	15,75	15,88	7,92	37,2	24,0	27,5	46,0	20,0	2,42	42,0	3,97
20B-G1	31,75	19,56	19,05	10,19	48,0	26,4	36,0	57,0	27,0	3,50	85,0	6,19
24B-G1	38,10	25,40	25,40	14,63	61,6	33,2	47,0	72,6	34,0	4,50	160,0	11,25


Roller chains with "U" type attachments



Reference	Pitch	Inner width	Roller diameter	Pin dimensions			Plate and "U" attachment dimensions					Breaking load	Weight per meter
DIN/ISO	P	B min	D1 max	D max	L max	H	A	C	H5	D4	T2	Q min	q
	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	KN	Kg/m
08B-U1	12,700	7,75	8,51	4,45	20,00	11,80	14,60	24,20	8,30	4,00	1,60	18,00	1,13
08B-U2	12,700	7,75	8,51	4,45	34,30	11,80	28,40	24,20	8,30	4,00	1,50	32,00	1,96
10B-U1	15,875	9,65	10,16	5,08	23,20	14,70	16,80	30,00	11,30	5,00	1,60	19,00	1,63
10B-U2	15,875	9,65	10,16	5,08	39,70	14,70	33,30	30,00	11,30	5,00	1,50	44,50	2,47
12B-U1	19,050	11,68	12,07	5,72	25,70	16,00	19,60	36,00	13,00	5,00	1,85	29,00	1,90
12B-U2	19,050	11,68	12,07	5,72	45,30	16,00	39,10	36,00	12,00	5,00	1,85	57,80	3,03
16A-U1	25,400	15,75	15,88	7,92	37,20	24,00	27,50	46,00	16,00	7,00	2,42	42,00	3,87
16B-U1	25,400	17,02	15,88	8,28	39,70	21,00	29,05	49,00	15,40	6,00	1,60	58,00	3,73
16B-U2	25,400	17,02	15,88	8,28	71,70	21,00	60,93	49,00	16,20	6,00	1,60	106,00	6,15
20B-U1	31,750	19,56	19,05	10,19	48,00	26,40	36,00	57,00	21,00	8,00	3,50	85,00	6,00
24B-U1	38,100	25,40	25,40	14,63	61,60	33,20	47,00	72,60	28,00	10,00	4,50	160,00	10,88

G Ö R G Ö S L Á N C O K

Double pitch roller chains



Double pitch roller chains / B series

Reference		Pitch	Inner width	Roller diameter	Pin diameter	Pin length		Plates width	Plates Thickness	Breaking load	Weight per meter
DIN/ISO	ANSI	P	B min	D1 max	D max	L max	Lo max	H max	T/T1 max	Q min	q
		mm	mm	mm	mm	mm	mm	mm	mm	KN	Kg/m
208A	2040	25,40	7,85	7,95	3,95	16,6	17,8	12,0	1,50	14,1	0,42
208B	2050	25,40	7,75	8,51	4,45	16,7	18,2	11,8	1,60	18,0	0,45
210A		31,75	9,40	10,16	5,08	20,7	22,2	15,0	2,03	22,2	0,73
210B	2060	31,75	9,65	10,16	5,08	19,5	20,9	14,7	1,70	22,4	0,65
212A		38,10	12,57	11,91	5,94	25,9	27,7	18,0	2,42	31,6	1,02
212B	2080	38,10	11,68	12,07	5,72	22,5	25,2	16,0	1,85	29,0	0,76
216A		50,80	15,75	15,88	7,92	32,7	36,5	24,0	3,25	56,7	1,70
216AH	2100	50,80	15,75	15,88	7,92	36,2	39,4	24,0	4,00	66,7	2,17
216B		50,80	17,02	15,88	8,28	36,1	39,1	21,0	4,15/3,1	60,0	1,75
220A	2120	63,50	18,90	19,05	9,53	40,4	44,7	30,0	4,00	88,5	2,55
220B		63,50	19,66	19,05	10,19	41,3	45,0	26,4	4,5/3,5	95,0	2,62
224A		76,20	25,22	22,23	11,10	50,3	54,3	35,7	4,80	127,0	4,06
224B		76,20	25,40	25,40	14,63	53,4	57,8	33,2	6,0/4,8	160,0	4,70
228B		88,90	30,99	27,94	15,90	65,1	69,5	36,7	7,5/6,0	200,0	6,23
232B		101,60	30,99	29,21	17,81	66,0	71,0	42,0	7,0/6,0	250,0	6,72

Double pitch roller chains



Attachment 90° 1 hole 1 side

A-1

Attachment 90° 1 hole 2 sides



K-1

Straight attachment 1 hole 1 side

SA-1

Straight attachment 1 hole 1 side

SK-1




Double pitch roller chains with attachments / B series

Reference		P	G	F	W	H4	D4	H2	H3	D9
DIN/ISO	ANSI									
		mm	mm	mm	mm	mm	mm	mm	mm	mm
208A	2040	25,40	19,1	25,4	39,6	9,1	3,4	11,1	20,5	5,5
210A	2050	31,75	23,8	31,8	49,0	11,1	5,5	14,3	25,0	6,6
212A	2060	38,10	28,6	42,9	67,8	14,7	5,5	17,5	32,9	9,2
216A	2080	50,80	38,1	55,6	87,8	19,1	6,8	22,2	43,5	11,0
220A	2100	63,50	47,6	66,6	107,5	23,4	9,2	28,6	50,4	13,0
224A	2120	76,20	57,2	79,3	127,5	27,8	10,5	33,3	55,5	15,0
208B	-	25,40	23,2	25,4	39,6	9,1	4,5	-	-	-
210B	-	31,75	23,8	31,8	49,0	11,1	5,5	-	-	-
212B	-	38,10	35,0	38,1	57,0	14,7	6,6	-	-	-
216B	-	50,80	44,0	50,8	84,0	19,1	6,6	-	-	-
220B	-	63,50	52,0	63,5	104,0	23,4	8,4	-	-	-
224B	-	76,20	60,0	76,2	120,0	27,8	10,5	-	-	-

G Ö R G Ö S L Á N C O K

Double pitch roller chains




Double pitch roller chains straight plates / A series


Reference		Pitch	Inner width	Roller diameter	Pin diameter	Pin length		Plates width	Plates thickness	Breaking load	Weight per meter
DIN/ISO	ASA	P mm	B min mm	D1 max mm	D max mm	L max mm	Lc max mm	H max mm	T max mm	Q min KN	q Kg/m
C208A	C2040	25,40	7,85	7,95	3,96	16,6	17,8	12,0	1,50	14,1	0,50
C208AL	C2042			15,88							0,84
C208AH	C2040H			7,95							0,85
C208AHL	C2042H			15,88							0,99
C210A	C2050	31,75	9,40	10,16	5,08	20,7	22,2	15,0	2,03	22,2	0,78
C210AL	C2052			19,05							1,27
C212A	C2060			11,91							1,12
C212AL	C2062			22,23							1,81
C212AH	C2060H	38,10	12,57	11,91	5,94	25,9	27,7	18,0	2,42	31,8	1,44
C212AHL	C2062H			22,23							2,07
C216A	C2080			15,88							2,08
C216AL	C2082			28,58							3,12
C216AH	C2080H	50,80	15,75	15,88	7,92	36,2	39,4	24,0	4,00	56,7	2,54
C216AHL	C2082H			28,58							3,58
C220A	C2100			19,05							3,01
C220AL	C2102			39,67							4,83
C220AH	C2100H	63,50	18,90	19,05	9,53	40,4	44,7	30,0	4,00	88,5	3,56
C220AHL	C2102H			39,67							5,38
C224A	C2120			22,23							4,86
C224AL	C2122			44,45							7,66
C224AH	C2120H	76,20	25,22	22,23	11,10	50,3	54,3	35,7	4,80	127,0	5,26
C224AHL	C2122H			44,45							8,26
C232A	C2160			28,58							8,15
C232AL	C2162			57,15							13,00
C232AH	C2160H	101,60	31,75	28,58	14,27	68,2	73,0	47,8	7,20	226,8	9,06
C232AHL	C2162H			57,15							12,77

Double pitch roller chains


Attachment 90° 1 Hole 1 side
A-1




Attachment 90° 2 Holes 1 side
A-2



Attachment 90° 1 Hole 2 sides
K-1



Attachment 90° 2 Holes 2 sides
K-2




Double pitch roller chains straight plates with attachments 90° / A series

Reference		P	G	P1	F	W	H4	D4
DIN/ISO	ANSI							
		mm	mm	mm	mm	mm	mm	mm
C208A	C2040	25,40	19,1	9,5	25,4	39,6	9,1	3,4
C208AL	C2042							
C210A	C2050	31,75	23,8	11,9	31,8	49,0	11,1	5,5
C210AL	C2052							
C212A	C2060	38,10	28,6	14,3	42,9	67,8	14,7	5,5
C212AL	C2062							
C212AH	C2060H	38,10	28,6	14,3	42,9	67,8	14,7	5,5
C212AHL	C2062H							
C216A	C2080	50,80	38,1	19,1	55,6	87,8	19,1	6,8
C216AL	C2082							
C216AH	C2080H	50,80	38,1	19,1	55,6	87,8	19,1	6,8
C216AHL	C2082H							
C220A	C2100	63,50	47,6	23,8	66,6	107,5	23,4	9,2
C220AL	C2102							
C220AH	C2100H	63,50	47,6	23,8	66,6	107,5	23,4	9,2
C220AHL	C2102H							
C224A	C2120	76,20	57,2	28,6	79,3	121,4	27,8	11,0
C224AL	C2122							
C224AH	C2120H	76,20	57,2	28,6	79,3	121,4	27,8	11,0
C224AHL	C2122H							
C232A	C2160	101,60	76,2	38,1	104,7	151,6	36,5	13,1
C232AL	C2162							
C232AH	C2160H	101,60	76,2	38,1	104,7	151,6	36,5	13,1
C232AHL	C2162H							


G Ö R G Ö S L Á N C O K

Double pitch roller chains


Straight attachment 1 hole 1 side
SA-1




Straight attachment 1 hole 2 sides
SK-1



Straight attachment 2 holes 1 side
SA-2




Straight attachment 2 holes 2 sides
SK-2



Double pitch roller chains straight plates with straight attachments / A series

Reference		P	G	P1	H2	H6	H3	D4	D9
DIN/ISO	ANSI								
C208A	C2040	25,40	19,1	9,5	11,1	13,5	20,5	3,4	5,5
C208AL	C2042								
C210A	C2050	31,75	23,8	11,9	14,3	15,9	25,0	5,5	6,6
C210AL	C2052								
C212A	C2060	38,10	28,6	14,3	17,5	19,1	32,9	5,5	9,2
C212AL	C2062								
C212AH	C2060H	38,10	28,6	14,3	17,5	19,1	32,9	5,5	9,2
C212AHL	C2062H								
C216A	C2080	50,80	38,1	19,1	22,2	25,4	43,5	6,6	11,0
C216AL	C2082								
C216AH	C2080H	50,80	38,1	19,1	22,2	25,4	43,5	6,6	11,0
C216AHL	C2082H								
C220A	C2100	63,50	47,6	23,8	28,6	31,8	50,4	8,4	13,0
C220AL	C2102								
C220AH	C2100H	63,50	47,6	23,8	28,6	31,8	50,4	8,4	13,0
C220AHL	C2102H								

Double pitch roller chains



Double pitch roller chains straight plates with hole / A series

Reference		P	B min	D1 max	D max	D4	L max	Lc max
DIN/ISO	ANSI							
C208A	C2040	25,40	7,85	7,95	3,96	4,1	16,6	18,8
C208AL	C2042			15,88				
C210A	C2050	31,75	9,40	10,16	5,08	5,1	20,7	23,3
C210AL	C2052			19,05				
C212A	C2060	38,10	12,57	11,91	5,94	6,1	25,9	28,3
C212AL	C2062			22,23				
C212AH	C2060H	38,10	12,57	11,91	5,94	6,1	29,2	31,6
C212AHL	C2062H			22,23				
C216A	C2080	50,80	15,75	15,88	7,92	8,1	32,7	36,5
C216AL	C2082			28,58				
C216AH	C2080H	50,80	15,75	15,88	7,92	8,1	36,2	39,4
C216AHL	C2082H			28,58				
C220A	C2100	63,50	18,90	19,05	9,53	10,1	40,4	44,7
C220AL	C2102			39,67				
C220AH	C2100H	63,50	18,90	19,05	9,53	10,1	43,8	46,9
C220AHL	C2102H			39,67				



G Ö R G Ö S L Á N C O K

Hollow pin chains



Type A fixed bush

Type B Roller




Hollow pin roller chain

Reference	Pitch	Inner width	Roller diameter	Pin diameter		Length Pin		Plates width	Plates thickness	Breaking load	Weight per meter	Type
	P	B min	D1 max	D max	D7 min	L max	Lo max	H max	T/T1 max	Q min	q	
	mm	mm	mm	mm	mm	mm	mm	mm	mm	KN	Kg/m	
08BHP	12,7	7,75	8,51	8,55	4,50	16,4	17,6	11,80	1,60/1,30	11,10	0,56	A
10BHP	15,875	9,65	10,16	7,02	5,13	19,5	20,5	14,7	1,70	10,00	0,86	A
12BHP	19,050	11,68	12,07	8,09	6,00	22,7	23,9	16,1	1,85	14,00	0,82	A
16BHP	25,4	17,02	15,88	11,50	8,20	35,3	37,0	23,2	4,0 / 3,1	49,00	2,26	A
40HP	12,7	7,85	7,95	5,63	4,00	16,5	17,6	12,0	1,60	11,00	0,54	A
50HP	15,875	9,40	10,16	7,03	5,13	20,7	21,9	15,09	2,03	20,00	0,91	A
60HP	19,05	12,70	11,91	8,31	6,00	25,8	26,8	18,0	2,42	24,00	1,29	A
80HP	25,4	15,75	15,88	11,40	8,05	32,5	33,8	24,0	3,25	50,00	2,26	A
70254HG000***	25,4	11	20	12	8,2	27	29	24	3	38,4	-	B
70254HTS04	25,4	17,02	15,88	8,05	4,2	28	30	14	2	19,2	-	B
70350HT000**	35	16	20	14	10,2	32	34	26	3	43	-	B
70381HG000***	38,1	12,7	25,4*	12	8,2	27	29	21	2,5	24	-	B
70417HG000***	41,75	20,5	17	11	8,2	36	38	22	3	38,4	-	B
70500HG001***	50	10	30*	12	8,2	26,5	28,5	26	3	51,5	-	B
70500HG008***	50	10	30	12	8,2	26,5	28,5	26	3	51,5	-	B
70508HT003**	50,8	10	30	11,6	8,2	26,5	28,5	26	3	51,5	-	B
70508HT004**	50,8	10	30*	11,5	8,2	26,5	28,5	26	3	51,5	-	B
71000HG005***	100	10	30	11,5	8,2	26,5	28,5	26	3	51,5	-	B

* POM roller ** Available in zinc plated *** Zinc plated

Hollow pin chains



Double pitch roller chains straight plates with hollow pin

Reference	Pitch	Inner width	Roller diameter	Pin diameter		Pin Length		Plates width	Plates thickness	Breaking load	Weight per meter
	P	B min	D1 max	D max	D7 min	L max	Lc max	H max	T max	Q min	q
	mm	mm	mm	mm	mm	mm	mm	mm	mm	KN	Kg/m
C2040H-HP***	25,400	7,85	7,95	5,63	4,00	16,50	17,60	12	1,50	11,00	0,46
C2050H-HP***	31,750	9,40	10,16	7,22	5,12	20,50	21,80	15	2,03	20,40	0,76
C2060H-HP***	38,100	12,70	11,91	8,31	6,00	25,80	26,80	17	2,42	24,00	1,02
C2080H-HP***	50,800	15,75	15,88	11,40	8,05	32,50	33,80	24	3,25	50,00	1,81
C2042H-HP	25,40	7,85	15,88	5,63	4,00	16,5	17,6	12	1,50	11,0	0,78
C2052H-HP	31,75	9,53	19,05	7,22	5,12	20,5	21,8	15	2,03	20,4	1,25
C2062H-HP	38,10	12,70	22,23	8,31	6,00	25,8	26,8	17	2,42	24,0	1,72
C2082H-HP	50,80	15,75	28,58	11,40	8,05	32,4	33,8	24	3,25	50,0	2,82
C2042H-H-HP	25,40	7,85	15,88	5,63	4,00	18,8	19,9	12	2,03	11,0	0,95
C2052H-H-HP	31,75	9,53	19,05	7,22	5,12	22,1	23,4	15	2,42	20,4	1,44
C2062H-H-HP	38,10	12,70	22,23	8,31	6,00	29,2	30,2	17	3,25	24,0	1,99
C2082H-H-HP	50,80	15,75	28,58	11,40	8,05	35,7	37	24	4,00	50,0	3,26
70500HT001	50	11,5	25	9	8,2	25	27	20	2,5	38	-
70500HT003***	50	15	18	14	10,2	36	38	26	4	57,6	-
70500HT009***	50	22	17	12	8	41	43	25	3	43,2	-
70500HG000**	50	15	31	14	10,2	36	38	25	4	51,2	-
70500HG004**	50	15	31*	14	10,2	31	33	25	3	38,4	-
70500HG007**	50	15	31	14	10,2	31	33	25	3	38,4	-
70630HG000**	63	18	30	14	10,2	35	37	25	3	33,6	-
70700HG000****	70	14	25	16	12,2	35,5	37,5	30	4	64	-
70700HG001**	70	15	30	16	12,2	36,5	38,5	35	4	84	-
70750HT000	75	15	31	14	10,2	36,5	38,5	25	4	51,2	-
70750HT001	75	15,5	28	14	8,5	37	39	35	4	102,4	-
70750HT003***	75	22	20	14	10,2	41	43	30	3	57,6	-
70800HG002**	80	24	42/50	16	10,2	45,5	47,5	30	4	64	-
71000HG001**	100	32	30	18	14,2	62	64	40	6	96,5	-
71000HG004**	100	15	30	16	12,2	36,5	38,5	35	4	96	-
71000HT000	100	15	31	14	10,2	36,5	38,5	25	4	51,2	-
71000HT005	100	22	40	18	12,2	45	47	35	4	83,2	-
71000HT014	100	25	40	25	20,2	52	54	50	5	160	-
71025HT000	102,5	15	30	17	8,5	37	39	40	4	115,2	-
71050HT000	105	15,5	30	20	14,5	38	40	40	4	96	-


* POM roller ** Zinc plated *** Fixed bush chain **** Nickel plated

G Ö R G Ö S L Á N C O K

Agricultural chains




Reference	Pitch	Inner width	Roller diameter	Pin diameter	Pin length	Plates Width	Plates thickness	Breaking load	Weight per meter
	P	B min	D1 max	D max	L max	H	T	Q	q
	mm	mm	mm	mm	mm	mm	mm	KN	Kg
S-32	29,21	15,88	11,43	4,45	26,7	13,2	1,8	15,00	0,86
S-42	34,93	19,05	14,27	7,00	34,3	19,8	2,8	27,00	1,60
S-45	41,40	22,23	15,24	5,72	37,7	17,3	2,8	18,00	1,66
S-52	38,10	22,23	15,24	5,72	37,7	17,3	2,8	18,00	1,68
S-55	41,40	22,23	17,78	5,72	37,7	17,3	2,8	18,00	1,80
S-62	41,91	26,20	19,05	5,72	40,3	17,3	2,5	26,70	1,87
S-77	58,34	22,23	18,26	8,90	43,2	26,2	4,0	45,00	2,66
S-88	66,27	28,58	22,86	8,90	49,8	26,2	4,0	45,00	3,25
C-550	41,40	19,81	16,87	7,19	35,0	19,3	2,8	30,10	1,94
C-620	42,01	24,51	17,81	7,19	41,8	20,2	3,25	30,10	2,35



Agricultural chains with attachments

Reference	Pitch	Inner width	Roller diameter	Pin diameter	Pin length	Attachment height	Hole width	Hole length	Distance between holes	Hole height	Attachment height	Breaking load
ISO	P	B min	D1 max	D max	L max	H4	D4	L2	F	H2	H3	KN
	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm
S-32	29,21	15,88	11,43	4,45	26,7	8,8	8,3	8,9	42,9	17,3	26,2	15,00
S-42	34,93	19,05	14,27	7,00	34,3	14	8,3	11,5	54,0	23,6	34,3	27,00
S-45	41,40	22,23	15,24	5,72	37,7	11,4	8,5	11,7	54,0	19,8	30,2	18,00
S-52	38,10	22,23	15,24	5,72	37,7	11,4	8,3	9,9	58,8	22,1	31,8	18,00
S-55	41,40	22,23	17,78	5,72	37,7	11,4	8,5	11,7	54,0	19,8	30,2	18,00
S-62	41,91	26,20	19,05	5,72	40,3	11,4	8,3	14,7	66,8	24,6	38,6	26,70
S-77	58,34	22,23	18,26	8,90	43,2	20,8	8,3	11,5	76,2	36,3	50,0	45,00
S-88	66,27	28,58	22,86	8,90	49,8	20,8	8,3	9,9	97,0	43,7	56,6	45,00

Stainless steel roller chains



Reference	Pitch	Inner width	Roller diameter	Pin diameter	Pin length		Plates width	Plates thickness	Breaking load	Weight per meter
DIN/ISO	P	B min	D1 max	D max	L max	Lc max	H max	T/T1 max	Q min	q
	mm	mm	mm	mm	mm	mm	mm	mm	KN	Kg/m
25SS*	6,350	3,18	3,30	2,31	7,9	8,4	6,00	0,8	2,5	0,15
35SS*	9,525	4,77	5,08	3,58	12,4	13,17	9,00	1,30	5,5	0,33
40SS	12,700	7,85	7,95	3,96	16,6	17,8	12,00	1,50	9,6	0,63
50SS	15,875	9,40	10,16	5,08	20,7	22,2	15,09	2,03	15,2	1,03
60SS	19,050	12,57	11,91	5,94	25,9	27,7	18,00	2,42	21,7	1,51
80SS	25,400	15,75	15,88	7,92	32,7	35,0	24,00	3,25	38,9	2,62
100SS	31,750	18,90	19,05	9,53	40,4	44,7	30,00	4,00	60,0	3,94
120SS	38,100	25,22	22,23	11,10	50,3	54,3	35,70	4,8	72,5	5,72
04BSS	6,000	2,80	4,00	1,85	6,80	7,8	5,00	0,60	2,0	0,11
05BSS	8,000	3,00	5,00	2,31	8,20	8,9	7,10	0,80	3,5	0,20
06BSS**	9,525	5,72	6,35	3,28	13,15	14,1	8,20	1,30	6,2	0,41
08BSS	12,700	7,75	8,51	4,45	16,7	18,2	11,80	1,60	12,0	0,70
10BSS	15,875	9,65	10,16	5,08	19,5	20,9	14,70	1,70	14,5	0,94
12BSS	19,050	11,68	12,07	5,72	22,5	24,2	16,00	1,85	18,5	1,16
16BSS	25,400	17,02	15,88	8,28	36,1	37,4	21,00	4,15/3,1	40,0	2,73
20BSS	31,750	19,56	19,05	10,19	41,3	45,0	26,40	4,5/3,5	59,0	3,73
24BSS	38,100	25,40	25,40	14,63	53,4	57,8	33,20	6,0/4,8	104,0	7,20
32BSS	50,8	30,99	29,21	17,81	66,0	71,0	42,00	7,0/6,0	160,0	10,22

* Fixed bush chain ** Straight plate


* Fixed bush chain ** Straight plate

ROZSDAMENTES LÁNCOK

Agricultural chains




Reference	Pitch	Inner width	Roller diameter	Pin diameter	Pin length	Plates Width	Plates thickness	Breaking load	Weight per meter
	P mm	B min mm	D1 max mm	D max mm	L max mm	H mm	T mm	Q KN	q Kg
S-32	29,21	15,88	11,43	4,45	26,7	13,2	1,8	15,00	0,86
S-42	34,93	19,05	14,27	7,00	34,3	19,8	2,8	27,00	1,60
S-45	41,40	22,23	15,24	5,72	37,7	17,3	2,8	18,00	1,66
S-52	38,10	22,23	15,24	5,72	37,7	17,3	2,8	18,00	1,68
S-55	41,40	22,23	17,78	5,72	37,7	17,3	2,8	18,00	1,80
S-62	41,91	26,20	19,05	5,72	40,3	17,3	2,5	26,70	1,87
S-77	58,34	22,23	18,26	8,90	43,2	26,2	4,0	45,00	2,66
S-88	66,27	28,58	22,86	8,90	49,8	26,2	4,0	45,00	3,25
C-550	41,40	19,81	16,87	7,19	35,0	19,3	2,8	39,10	1,94
C-620	42,01	24,51	17,81	7,19	41,8	20,2	3,25	39,10	2,35



Agricultural chains with attachments

Reference	Pitch	Inner width	Roller diameter	Pin diameter	Pin length	Attachment height	Hole width	Hole length	Distance between holes	Hole height	Attachment height	Breaking load
ISO	P mm	B min mm	D1 max mm	D max mm	L max mm	H4 mm	D4 mm	L2 mm	F mm	H2 mm	H3 mm	KN
S-32	29,21	15,88	11,43	4,45	26,7	8,8	5,3	6,9	42,9	17,3	26,2	15,00
S-42	34,93	19,05	14,27	7,00	34,3	14	8,3	11,5	54,0	23,6	34,3	27,00
S-45	41,40	22,23	15,24	5,72	37,7	11,4	8,5	11,7	54,0	19,8	30,2	18,00
S-52	38,10	22,23	15,24	5,72	37,7	11,4	8,3	9,9	58,8	22,1	31,8	18,00
S-55	41,40	22,23	17,78	5,72	37,7	11,4	8,5	11,7	54,0	19,8	30,2	18,00
S-62	41,91	26,20	19,05	5,72	40,3	11,4	8,3	14,7	60,8	24,6	38,6	26,70
S-77	58,34	22,23	18,26	8,90	43,2	20,8	8,3	11,5	76,2	36,3	50,0	45,00
S-88	66,27	28,58	22,86	8,90	49,8	20,8	8,3	9,9	97,0	43,7	55,6	45,00

Stainless steel roller chains




Reference	Pitch	Inner width	Roller diameter	Pin diameter	Pin length		Plates width	Plates thickness	Breaking load	Weight per meter
DIN/ISO	P	B min	D1 max	D max	L max	Lc max	H max	T/T1 max	Q min	q
	mm	mm	mm	mm	mm	mm	mm	mm	KN	Kg/m
25SS*	6,350	3,18	3,30	2,31	7,9	8,4	6,00	0,8	2,5	0,15
35SS*	9,525	4,77	5,08	3,58	12,4	13,17	9,00	1,30	5,5	0,33
40SS	12,700	7,85	7,95	3,96	16,6	17,8	12,00	1,50	9,6	0,63
50SS	15,875	9,40	10,16	5,08	20,7	22,2	15,09	2,03	15,2	1,03
60SS	19,050	12,57	11,91	5,94	25,9	27,7	18,00	2,42	21,7	1,51
80SS	25,400	15,75	15,88	7,92	32,7	35,0	24,00	3,25	38,9	2,62
100SS	31,750	18,90	19,05	9,53	40,4	44,7	30,00	4,00	60,0	3,94
120SS	38,100	25,22	22,23	11,10	50,3	54,3	36,70	4,8	72,5	5,72
04BSS	6,000	2,80	4,00	1,85	6,80	7,8	5,00	0,60	2,0	0,11
05BSS	8,000	3,00	5,00	2,31	8,20	8,9	7,10	0,80	3,5	0,20
06BSS**	9,525	5,72	6,35	3,28	13,15	14,1	8,20	1,30	6,2	0,41
08BSS	12,700	7,75	8,51	4,45	16,7	18,2	11,80	1,60	12,0	0,70
10BSS	15,875	9,65	10,16	5,08	19,5	20,9	14,70	1,70	14,5	0,94
12BSS	19,050	11,68	12,07	5,72	22,5	24,2	16,00	1,85	18,5	1,16
16BSS	25,400	17,02	15,88	8,28	36,1	37,4	21,00	4,15/3,1	40,0	2,73
20BSS	31,750	19,56	19,05	10,19	41,3	45,0	26,40	4,5/3,5	59,0	3,73
24BSS	38,100	25,40	25,40	14,63	53,4	57,8	33,20	6,0/4,8	104,0	7,20
32BSS	50,8	30,99	29,21	17,81	66,0	71,0	42,00	7,0/6,0	150,0	10,22

* Fixed bush chain ** Straight plate

ROZSDAMENTES LÁNCOK

Stainless steel double pitch chains




Small roller type

Big roller type

Reference	Pitch	Inner width	Roller diameter	Pin diameter	Pin length	Plates width	Plates thickness	Breaking load	Weight per meter	
ASA	P	B min	D1 max	D max	L max	Lc max	H max	T max	Q min	q
	mm	mm	mm	mm	mm	mm	mm	mm	KN	Kg/m
C2040SS	25,40	7,85	7,95	3,96	16,6	17,6	12,0	1,50	9,6	0,51
C2042SS			15,88							0,85
C2040HSS	25,40	7,85	7,95	3,96	18,8	19,9	12,0	2,03	9,6	0,66
C2042HSS			15,88							0,99
C2050SS	31,75	9,40	10,16	5,08	20,7	22,2	15,0	2,03	15,2	0,79
C2052SS			19,05							1,29
C2060SS	38,10	12,57	11,91	5,94	25,9	27,7	18,0	2,42	21,7	1,13
C2062SS			22,23							1,63
C2060HSS	38,10	12,57	11,91	5,94	29,2	31,6	18,0	3,25	21,7	1,46
C2062HSS			22,23							2,10
C2080SS	50,80	15,75	15,88	7,92	32,7	36,5	24,0	3,25	38,9	2,11
C2082SS			28,58							3,16
C2080HSS	50,80	15,75	15,88	7,92	36,2	39,4	24,0	4,00	38,9	2,57
C2082HSS			28,58							3,83
C2100SS	63,50	18,90	19,05	9,53	40,4	44,7	30,0	4,00	60,0	3,05
C2102SS			39,67							4,89
C2100HSS	63,50	18,90	19,05	9,53	43,6	46,9	30,0	4,80	60,0	3,61
C2102HSS			39,67							5,45

Stainless steel hollow pin chains




Stainless steel hollow pin roller chains

Reference	Pitch	Inner width	Roller diameter	Pin diameter		Length pin		Plates width	Plates thickness	Breaking load	Weight per meter	Type
	P mm	B min mm	D1 max mm	D max mm	D7 min mm	L max mm	Lc max mm	H max mm	T/T1 max mm	Q min kN	q kg/m	
40HPSS	12,700	7,85	7,95	5,63	4,00	16,50	17,60	12,00	1,50	7,70	0,55	A
50HPSS	15,875	9,40	10,16	7,03	5,13	20,70	21,90	15,09	2,03	14,0	0,92	A
60HPSS	19,050	12,70	11,91	8,31	6,00	25,80	26,80	18,00	2,42	16,8	1,31	A
80HPSS	25,400	15,75	15,88	11,40	8,06	32,50	33,80	24,00	3,25	35,0	2,29	A
08BHPSS	12,700	7,75	8,51	6,55	4,50	16,40	17,60	11,80	1,6/1,3	7,80	0,57	A
10BHPSS	15,875	9,65	10,16	7,02	5,13	19,5	20,5	14,7	1,7	11,9	0,86	A
12BHPSS	19,050	11,68	12,07	8,09	6	22,70	23,9	16,1	1,85	15,3	0,82	A
16BHPSS	25,400	17,02	15,88	11,5	8,2	35,3	37,0	23,2	4,0/3,1	36,7	2,26	A
70254HI001	25,400	17,02	15,88	8,00	6,20	33,00	35,00	21,00	3,00	36,3	-	A
70254HI004	25,400	8,00	16,00	6,00	4,20	19,20	20,70	12,00	2,00	8,8	-	B
70317HI002	31,750	11,00	20,00	7,00	4,20	23,00	24,50	16,50	2,00	16,5	-	B
70317HI004	31,750	19,56	19,05	10,20	6,20	40,00	42,00	26,00	4,00	55,0	-	A
70350HI000	35	16	20	14	10,2	32	34	26	3	29,7	-	B
70417HI000	41,750	20,5	17	11	8,2	36	38	22	3	26,4	-	B
70508HI000*	50,8	10	30	11,5	8,2	26,5	28,5	26	3	46,2	-	B

* Available with POM roller

ROZSDAMENTES LÁNCOK


Stainless steel hollow pin chains



Stainless steel roller chains with straight plates and hollow pin


Reference	Pitch	Inner width	Roller diameter	Pin diameter		Pin length		Plates width	Plates thickness	Breaking load	Weight per meter
	P	B min	D1 max	D max	D7 min	L max	Lc max	H max	T/T1 max	Q min	q
	mm	mm	mm	mm	mm	mm	mm	mm	mm	KN	Kg/m
C2040HPSS**	25,4	7,85	7,95	5,83	4,00	16,5	17,6	12	1,5	7,7	0,47
C2050HPSS**	31,75	9,40	10,16	7,22	5,12	20,5	21,8	15	2,03	14,3	0,77
C2060HPSS**	38,1	12,70	11,91	8,31	6,00	25,8	26,8	17	2,42	16,8	1,03
C2080HPSS**	50,8	15,75	15,88	11,40	8,06	32,5	33,8	24	3,26	35,0	1,83
C2042HPSS	25,4	7,85	15,88	5,83	4,00	16,5	17,6	12	1,5	7,70	0,79
C2052HPSS	31,75	9,53	19,05	7,22	5,12	20,5	21,8	15	2,03	14,3	1,27
C2062HPSS	38,1	12,70	22,23	8,31	6,00	25,8	26,8	17	2,42	16,8	1,74
C2082HPSS	50,8	15,75	58,58	11,40	8,06	32,4	33,8	24	3,26	35,0	2,86
C2042H-HPSS	25,4	7,85	15,88	5,83	4,00	18,8	19,9	12	2,03	7,70	0,96
C2052H-HPSS	31,75	9,53	19,05	7,22	5,12	22,1	23,4	15	2,42	14,3	1,46
C2062H-HPSS	38,1	12,70	22,23	8,31	6,00	29,2	30,2	17	3,26	16,8	2,02
C2082H-HPSS	50,8	15,75	58,58	11,40	8,06	36,2	37,6	24	4	35,0	3,3
70254HIS06	25,4	9,53	10,16	7,20	5,1	20	21,5	16	2	13,2	-
70413HI000	41,3	14	30*	12,00	10,2	30,5	32	24	3	29,7	-
70500HI000	50	15	31	14	10,2	36	38	25	4	36,2	-
70500HI002	50	11,5	25	9	8,2	25	27	20	2,5	24,7	-
70800HI000	80	24	42/50	16	10,2	45,5	47,5	30	4	44	-
71000HI002	100	21	52	18	14,2	45	47	40	5/4	96,8	-

* POM roller ** Fixed bush



CONVEYOR LÁNCOK

Leaf chains AL series



SZÁLLÍTÓLÁNCOK


Rajz vagy minta alapján
bármilyen láncot gyártunk.

Reference	Pitch	Plates lacing	Plates width H max	Plates thickness T max	Pin diameter D max	Pin length L max	Breaking load Q min	Weight per meter q
ASA	P		mm	mm	mm	mm	KN	Kg/m
AL322	9,525	2 x 2	7,7	1,30	3,58	6,80	9,00	0,23
AL344		4 X 4				11,60	18,0	0,46
AL422	12,700	2 X 2	10,4	1,50	3,96	8,30	14,10	0,39
AL444		4 X 4				14,40	28,20	0,74
AL466		6 X 6				20,50	42,30	1,13
AL522	15,875	2 X 2	12,8	2,03	5,08	11,05	22,00	0,64
AL534		3 X 4				17,00	33,00	1,10
AL544		4 X 4				19,40	44,00	1,25
AL566		6 X 6				27,50	66,00	1,79
AL622	19,050	2 X 2	15,6	2,42	5,94	13,00	37,00	0,86
AL644		4 X 4				22,70	66,70	1,76
AL666		6 X 6				32,20	100,10	2,60
AL688		8 X 8				42,20	133,40	3,49
AL822	25,400	2 X 2	20,5	3,25	7,92	16,20	56,70	1,54
AL844		4 X 4				29,40	113,40	3,00
AL866		6 X 6				44,20	170,00	4,46
AL1022	31,750	2 X 2	25,6	4,00	9,53	19,60	88,50	2,37
AL1044		4 X 4				36,40	177,00	4,68
AL1066		6 X 6				52,30	265,00	7,20
AL1088		8 X 8				66,50	354,00	9,94
AL1222	38,100	2 X 2	30,5	4,80	11,10	24,30	127,00	3,66
AL1244		4 X 4				43,80	254,00	7,05
AL1266		6 X 6				63,20	381,00	10,50
AL1288		8 X 8				82,60	508,00	14,03
AL1444	44,450	4 X 4	36,4	5,60	12,64	51,30	372,70	10,34
AL1466		6 X 6				74,58	559,00	15,16
AL1644	50,800	4 X 4	41,6	6,40	14,21	58,00	471,00	12,98
AL1666		6 X 6				83,80	706,00	19,76
AL1688		8 X 8				109,50	942,0	25,47



CONVEYOR LÁNCOK


Conveyor chains M series



Reference	Standard pitches					Inner width		Bush diameter		Rollers			Plates		Pins		Breaking load
	P ^m mm					B min mm	D6 mm	D1 mm	D2 mm	D5 mm	H mm	T/T1 mm	width mm	thickness mm	diameter mm	Length mm	
ISO																	Q min kN
M-20	40	50	63	80	100	125	16	9	12,5	25	30	18	2,5	6	31	20	
M-28	50	63	80	100	125	160	18	10	15	30	36	20	3	7	35	28	
M-40	63	80	100	125	160	200	20	12,5	18	36	42	25	4/3	8,5	41	40	
M-56	80	100	125	160	200	250	24	15	21	42	50	30	4	10	46	56	
M-80	100	125	160	200	250	315	28	18	25	50	60	36	5	12	55	80	
M-112	125	160	200	250	315	400	32	21	30	60	70	40	6	15	64	112	
M-160	160	200	250	315	400	500	37	25	36	70	85	50	7	18	74	160	
M-224	200	250	315	400	500	630	43	30	42	85	100	60	8	21	85	224	
M-315	250	315	400	500	630	800	48	36	50	100	120	70	10	25	100	315	
M-450	315	400	500	630	800	1000	56	42	60	120	140	80	12	30	118	450	
M-630	400	500	630	800	1000	1250	66	50	70	140	170	100	15	36	138	630	
M-900	500	630	800	1000	1250	1600	78	60	85	170	210	120	15	44	160	900	

* Other pitches on demand


Conveyor chains with attachments M series



Reference	Attachment height	Distance between holes	Total width	Hole diameter	1 hole		2 holes									Iron angle
					P min	G	short			normal			long			
							P min	P1	G	P min	P1	G	P min	P1	G	
ISO	H4	P	W	D4												
	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	
M-20	16	54	78	8,6	40	14	63	20	35	80	35	50	100	50	65	L25x3
M-28	20	64	92	9	50	20	80	20	45	100	40	60	125	65	85	L30x3
M-40	25	70	116	9	63	20	80	20	40	100	40	60	125	65	85	L40x4
M-56	30	88	132	11	63	22	100	25	50	125	50	75	160	85	110	L45x4
M-80	35	96	150	11	80	22	125	50	75	160	85	110	200	125	150	L50x5
M-112	40	110	180	14	80	28	125	35	65	160	85	95	200	100	130	L60x6
M-160	45	124	210	14	100	30	160	60	80	200	85	115	250	145	175	L70x7
M-224	55	140	240	18	125	35	200	65	100	250	125	160	315	190	225	L80x8
M-315	65	160	290	18	160	35	200	50	85	250	100	135	315	155	190	L100x10
M-450	75	180	350	18	200	40	250	85	125	315	155	195	400	240	280	L120x12
M-630	90	230	370	24	250	50	315	100	150	400	190	240	500	300	350	L120x12
M-900	110	280	440	30	250	60	315	65	125	400	155	215	500	240	300	L160x15

CONVEYOR LÁNCOK


Conveyor chains MT series



Reference	Standard pitches							Inner width	Bush diameter	Roller	Plates			Pins		Breaking load
											width	deep	thickness	diameter	length	
ISO	P ^a mm							B min mm	D6 mm	D2 mm	H mm	H1 mm	T/T1 mm	D mm	L max mm	Q min kN
MT20	40	50	63	80	100	125	160	16	9	25	25	16	2,5	6	31	20
MT28	50	63	80	100	125	160	200	18	10	30	30	20	3	7	35	28
MT40	63	80	100	125	160	200	250	20	12,5	36	36	22,5	4/3	8,5	41	40
MT56	80	100	125	160	200	250	315	24	15	42	45	30	4	10	46	56
MT80	100	125	160	200	250	315	400	28	18	50	50	32,5	5	12	55	80
MT112	125	160	200	250	315	400	500	32	21	60	60	40	6	15	64	112
MT160	160	200	250	315	400	500	630	37	25	70	70	45	7	18	74	160
MT224	200	250	315	400	500	630	800	43	30	85	90	60	8	21	85	224
MT315	250	315	400	500	630	800	1000	48	36	100	100	65	10	25	100	315
MT450	-	200	250	315	400	500	630	56	42	120	120	80	12	30	118	450
MT630	-	200	250	315	400	500	630	66	50	140	140	90	15	38	158	630
MT900	-	-	250	315	400	500	630	78	60	170	180	120	15	44	160	900

* Other pitches on demand

Conveyor chains MC series




Reference	Standard pitches						Inner width	Bush diameter	Rollers			Plates		Pins			Breslow load
									small	big	flange	width	thickness	outer diameter	inner diameter	length	
ISO	P"						B min	D6	D1	D2	D5	H	T/T1	D	D7 min	L max	Q min
	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	KN
MC-28	63	80	100	125	160	200	20	16	25	36	42	25	4/3	12	8,2	42	28
MC-56	80	100	125	160	200	250	24	20	30	50	60	35	4	16	10,2	46,5	56
MC-112	100	125	160	200	250	320	30	30	42	70	85	50	6	22	14,3	64	112
MC-224	160	200	250	315	400	430	40	40	60	100	120	70	8	30	20,3	85	224

* Other pitches on demand

CONVEYOR LÁNCOK


Conveyor chains FV series



Reference	Standard pitches						Inner with	Bush diameter	Rollers				Plates		Pins		Breaking load	
	P*								D1	D2	D3	D5	H	T	D	L max		
ISO	mm						B min mm	D6 mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	Q min kN
FV-40	40	63	80	100	-	-	18	15	20	32	40	48	25	3	10	37	40	
FV-63	40	63	80	100	125	160	22	18	26	40	50	60	30	4	12	46	63	
FV-90	63	80	100	125	160	200	25	20	30	48	60	73	35	5	14	53	90	
FV-112	80	100	125	160	200	250	30	22	32	55	72	87	40	6	16	63	112	
FV-140	100	125	160	200	250	315	35	26	36	60	80	96	45	8	18	68	140	
FV-180	125	160	200	250	315	400	45	30	42	70	100	120	50	8	20	86	180	
FV-250	125	160	200	250	315	400	55	36	50	80	125	145	60	8	26	96	250	
FV-315	-	160	200	250	315	400	65	42	60	90	140	170	70	10	30	117	315	
FV-400	-	160	200	250	315	400	70	45	60	100	150	185	70	12	32	131	400	
FV-500	-	160	200	250	315	400	80	50	70	110	160	195	80	12	36	141	500	
FV-630	-	-	160	200	315	400	90	56	80	120	170	210	100	12	42	153	630	

* Other pitches on demand


Conveyor chains with attachments FV series



Reference	Attachment height	Distance between holes	Total width	Hole diameter	1 hole			2 holes								Iron angle	
					P min	G	short			normal			long				
ISO	H4	F	W	D4			P min	G	P min	P1	G	P min	P1	G	P min	P1	G
	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm
FV-63	30	68	100	9	63	40	100	30	50	125	40	60	160	50	60		L30x3
FV-90	35	80	130	9	-	-	100	30	50	125	40	60	160	50	70		L40x4
FV-112	40	100	148	11	-	-	100	30	50	125	40	65	160	50	75		L45x5
FV-140	45	100	170	11	-	-	100	30	55	125	40	65	160	50	75		L50x5
FV-180	45	128	200	13,5	-	-	125	35	65	160	50	80	200	65	95		L60x6
FV-250	55	138	230	13,5	125	60	160	50	80	200	65	95	250	80	110		L70x7
FV-315	60	170	270	13,5	160	60	200	65	95	250	80	110	315	100	130		L80x8
FV-400	65	190	325	18	160	60	200	60	100	250	80	120	315	100	140		L100x10
FV-500	70	200	335	18	160	60	200	60	90	250	80	120	315	100	140		L100x10
FV-630	80	230	365	18	200	60	250	70	110	315	100	140	400	100	140		L120x12

CONVEYOR LÁNCOK


Conveyor chains
FVT series



Reference	Standard pitches						Inner with	Bush diameter	Roller	Plates			Pins		Breaking load
										width	deep	thickness	diameter	length	
ISO	P* mm						B min mm	D6 mm	D2 mm	H mm	H1 mm	T mm	D mm	L max mm	Q min kN
FVT40	40	63	80	100	-	-	18	15	32	35	22	3	10	37	40
FVT63	40	63	80	100	125	160	22	18	40	40	25	4	12	46	63
FVT90	63	80	100	125	160	200	25	20	48	45	27,5	5	14	53	90
FVT112	80	100	125	160	200	250	30	22	55	50	30	6	16	63	112
FVT140	100	125	160	200	250	315	35	26	60	60	37,5	6	18	66	140
FVT180	125	160	200	250	315	400	45	30	70	70	45	8	20	86	180
FVT250	125	160	200	250	315	400	55	36	80	80	50	8	26	96	250
FVT315	-	160	200	250	315	400	65	42	90	90	55	10	30	117	315
FVT400	-	160	200	250	315	400	70	45	100	90	55	12	32	131	400
FVT500	-	160	200	250	315	400	80	50	110	100	60	12	36	141	500
FVT630	-	-	160	200	315	400	90	56	120	120	70	12	42	163	630

* Other pitches on demand

Conveyor chains
FVC series




Reference	Standard pitches						Inner with	Bush diameter	Rollers				Plates		Pins			Breaking load
									small	big	rolling	flange	width	thickness	outer diameter	inner diameter	length	
ISO	P*						B min	D6	D1	D2	D3	D5	H	T	D	D7 min	L max	Q min
	mm						mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	kN
PVC63	40	63	80	100	125	160	22	18	26	40	60	60	30	4	12	8,2	46	57
PVC90	63	80	100	125	160	200	25	20	30	48	63	73	35	5	14	10,2	53	73
PVC112	80	100	125	160	200	250	30	22	32	55	72	87	40	6	16	11,2	63	102
PVC140	100	125	160	200	250	315	35	26	36	60	80	95	45	6	18	12,2	66	136
PVC180	125	160	200	250	315	400	45	30	42	70	100	120	50	8	20	14,3	86	154
PVC250	125	160	200	250	315	400	55	36	50	80	125	145	60	8	26	18,3	98	230
PVC315	-	160	200	250	315	400	65	42	60	90	140	170	70	10	30	20,3	117	338

* Other pitches on demand

CONVEYOR LÁNCOK


Conveyor chains Y series



Yuk reference	Standard pitches	Inner width	Bush diameter	Roller		Plates		Pin		Breaking load
				big diameter	flange diameter	width	thickness	diameter	length	
	P ^a mm	B min mm	D6 mm	D2 mm	D5 mm	H mm	T/T1 mm	D mm	L max mm	Q min kN
Y1	50,8 - 63,5 - 76,2 - 88,9 - 101,6 - 127,0 - 152,4	15	14	31,75	40,0	25	4	10	37	52,8
Y2	76,2 - 88,9 - 101,6 - 127,0 - 152,4 - 177,8 - 203,2	19	20	47,5	60,0	40	5/4	14	45	120,0
Y3	101,6 - 127,0 - 152,4 - 177,8 - 203,2 - 228,6	26	24	66,7	82,0	60	7/5	18	68	192,0
Y4	152,4 - 177,8 - 203,2 - 254,0	38	30	88,9	114,0	80	10/8	22	84	360,0

* Other pitches on demand

Conveyor chains YT series




Yuk reference	Standard pitches	Inner width	Bush diameter	Roller diameter	Plates			Pin		Breaking load
					width	deep	thickness	diameter	length	
	P ^a mm	B min mm	D6 mm	D2 mm	H mm	H1 mm	T/T1 mm	D mm	L max mm	Q min kN
YT1	50,8 - 63,5 - 76,2 - 88,9 - 101,6 - 127,0 - 152,4	15	14	31,75	40	27	4	10	37	52,8
YT2	76,2 - 88,9 - 101,6 - 127,0 - 152,4 - 177,8 - 203,2	19	20	47,5	60	30	5/4	14	45	120,0
YT3	101,6 - 127,0 - 152,4 - 177,8 - 203,2 - 228,6 - 254,0	26	24	66,7	70	45	7/5	18	68	192,0
YT4	152,4 - 177,8 - 203,2 - 254,0 - 304,8	38	30	88,9	90	60	10/8	22	84	360,0

* Other pitches on demand

CONVEYOR LÁNCOK




Conveyor chains Series YC



Yuk reference	Standard pitches	Inner width	Bush diameter	Roller		Plates		Pins			Breaking load
				big diameter	flange diameter	width	thickness	outer diameter	inner diameter	length	
	P [*] mm	B min mm	D6 mm	D2 mm	D5 mm	H mm	T/T1 mm	D mm	D7 min mm	L max mm	Q min kN
YC1	50,8 - 63,5 - 76,2 - 88,9 - 101,6 - 127,0 - 152,4	15	18	31,75	40,0	25	4	14	10,2	37	40,0
YC2	76,2 - 88,9 - 101,6 - 127,0 - 152,4 - 177,8 - 203,2	19	22	47,5	60,0	40	5/5	18	13,2	45	105,8
YC3	101,6 - 127,0 - 152,4 - 177,8 - 203,2 - 228,6 - 254,0	25	35	66,7	82,0	50	7/5	30	20,2	58	142,8
YC4	152,4 - 177,8 - 203,2 - 254,0 - 304,8	35	35	88,9	114,0	60	10/8	30	22,2	83	288,0

* Other pitches on demand

Non standard conveyor chains




Conveyor chains

Yuk reference	Pitch	Inner with	Roller diameter	Plates		Pins		Breaking load		Type
	P* mm	B min mm	D2 mm	width	thickness	diameter	length	Q min kN		
				H mm	T/T1 mm	D mm	L max mm			
70350LT003	35	14	14	18	3,5/2,5	7	31	37	A	
70350LT004*	35	14	14	18	3	6	30,2	38,4	A	
70350LT005	35	14	22	18	3,5/2,5	7	31	37	B	
70350LT006	35	16	20	18	2,5	7	31	32	B	
70350LG000**	35	16	14	18	2,5	7	31	32	A	
70413LT000	41,3	12	16	22	2,5	9	27	40	A	
70413LT001***	41,3	10	16	21	3	9	27	43,2	A	
70413LT002	41,3	16	16	30	3	9	33	61	A	
70413LG001**	41,3	16	16	21	3	9	33	43,2	A	
70414LT001	41,4	22,23	17,9	20	3,4/2,7	8,22	39,3	47,3	A	
70500LT000	50	15	31	25	4	10	38	75,4	B	
70500LT004	50	11,5	25	18	2,5	5,7	28	24,5	A	
70500LT006	50	11,5	25	20	3	8	28	43,2	B	
70500LT010	50	15	31	23	3	10	33	48	B	
70500LT013	50	16	25	18	2,5	6	31	27,2	B	
70500LT014	50	16	20	25	3	7	33	37	A	
70500LT015	50	25,4	25,4	40	5	14,83	54	161	A	
70506LT012	50,8	16	25	20	3	7	33	37	B	
70508LT016	50,8	17,02	15,88	20	4/3	8,28	35,1	54,4	A	
70630LT006*	63	18	15	25	4	10	40	75,4	A	


* Fixed bush chain ** Zinc plated *** Available in zinc plated

CONVEYOR LÁNCOK

Non standard conveyor chains



Attachment 1 side



Attachment 2 sides

Conveyor chains with attachments 2 sides



Yuk reference	Pitch	Inner with		Roller diameter		Plates		Pins		Attachments								Breaking load																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																											
						width	thickness	diameter	length	width	height	distance between holes	H	F	p- Holes	holes pitch	holes diameter		Pitch between attachments																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																										
		P	B min	D2	H															T/T1	D	L max	G	H4	F	P1	D4	Q min																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																	
		mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm		mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm

* Fixed bush chain

Conveyor chains with attachments 1 side

Yuk reference	Pitch	Inner with		Roller diameter	Plates		Pins		Attachments								Breaking load
					width	thickness	diameter	length	width	height	distance of hole	H° holes	holes pitch	holes diameter	Pitches between attachments		
		P mm	B min mm	D2 mm	H mm	T/T1 mm	D mm	L max mm	G mm	H4 mm	F/2 mm	P1 mm	D4 mm	Q min KN			
70500AT001	50	11,5	25	15	3	5,7	28	41	25	24	1	-	6,5	2	24,5		
70500AT002	50	11,5	25	18	2,5	5,7	26	46	24	22	1	-	6,5	2	24,5		
70500AT003	50	15	31	25	4	10	36	35	20,5	27	1	-	10,5	2	70,4		
70500AT006	50	15	31	23	3	10	33	30	28	31	1	-	10	1	47		
70500AT007	50	11,5	25	18	2,5	5,7	26	46	24	22	1	-	6,5	1	24,5		
70500AT009	50	15	31	23	3	10	33	60	35	31	1	-	10	2	47		
70500AT017	50	12	15	15	2	6	25	30/40	20	25	1	-	8	2	21,8		
70600AT000	63	18	30	20	3	7	35	25	20	32	1	-	9	6	37		
70690AT000	69	12	25	19	2,5	7	27	60	25,5	25	1	-	7	2	36		
70690AT001	69	12	25	19	2,5	7	27	60	25,5	25	1	-	7	1	36		
70750AT000	75	22	30	40	6/8	14	-	50	36	48	1	-	12,5	4	147		
70800AG000	80	20	50	35	5	12	47	50	26,25	37 / 54,5	2	17,5	8,25	8	108,6		
71000AT001	100	25	45	35	6/5	14,6	55	50	2,5	54,5	1	-	12,5	2	158,4		
71000AT010	100	28	35	50	6	16	59	60	40	53	2	25	11	1	244		
71250AT009	125	25	45/56	35	6/5	14,6	55	60	35	45	2	30	11	1	158,4		
71250AT011	125	32	60	40	6	15	64	65	12	55	1	-	11X23	1	169,9		
71250AT016	125	25	45/56	35/100	6/5	14,6	55	75	30	47,5	2	50	13	1	158,4		
72000AT001	200	37	60/75	45/100	6	16	69	120	6	55,5	2	90	13	1	193		
72000AT003	200	37	60/75	45	6	16	69	120	40	51	2	90	11	1	193		
72000AT004	200	37	60/75	50/100	6	18	69	120	6	55,5	2	90	13	1	244		
72000AT006	200	33	75/90	60	10/8	22	77	120	40	57,5	2	90	11	1	365		
72000AT007	200	37	60/75	45	6	16	75	120	40	51	2	90	11	1	193		

Non standard conveyor chains



T/P - Extended pin on every pitches
C/2 - Extended pin on every 2 pitches
C/4 - Extended pin on every 4 pitches
For other measures, please consult


Conveyor chains with extended pins

Yuk reference	Pitch	Inner width	Roller diameter	Plates		Pins		Extended pin		Breaking load	Type
	P	B min	D2	H	thickness T/T1	diameter D	length L max	diameter D8	length L1	Q min	
	mm	mm	mm	mm	mm	mm	mm	mm	mm	kN	
70350PT000**	35	16	20	18	2,5	7	31	10	30	32	C/2
70350PT001*	35	16	20	18	2,5	7	-	10	30	32	T/P
70350PT002*	35	16	14	18	2,5	7	31	10	30	32	C/2
70350PT003	35	10	20	18	3/2,5	7	26	10	30	37	C/2
70350PT004	35	16	20	18	3	8	33	10	25	33,6	C/4
70350PG000***	35	16	20	26	2,5	10	31	10	35	52	C/2
70381PG001***	38,1	16	20	18	2,5	7	-	10	30	32	T/P
70413PT000	41,3	10	25	22	3	9	27	12	30	46	C/2
70413PT001	41,3	12	16	22	2,5	9	-	10	25	40	T/P
70413PT002	41,3	16	16	22	3	9	33	12	40	46	C/2
70413PT003	41,3	16	25	22	3	9	33	12	40	46	C/2
70413PT004	41,3	10	25	22	3	9	-	10	25	46	T/P
70413PG000***	41,3	10	25	22	3	9	27	12	40	46	C/2
70419PG000***	41,9	25,4	19,05	26	3	8	42,5	12,7	40	48,3	C/2

* Available in zinc plated ** Available in nickel plated *** Zinc plated **** Shape "B" plates & zinc plated

CONVEYOR LÁNCOK

Non standard conveyor chains







Deep plates conveyor chains

Yuk reference	Pitch	Inner with	Roller diameter	Plates			Pins		Breaking load
	P	B min	D2	width	deep	thickness	diameter	length	
	mm	mm	mm	H	H1	T	D	L max	Q min
	mm	mm	mm	mm	mm	mm	mm	mm	KN
70600LT002	50	15	31	30	17,5	4	10	36	75,4
70600LT007	50	11,5	18	17,5	10	2,5	5,7	25,5	24,5
70600LT011	50	11,5	25	25	16,5	2	5,7	24	24,5
70606LT011	50,8	15	31,75	40	27	4	14	37	57,6
70630LG000*	63	16	30	30	19	4	8,5	37	54,5

* Zinc plated

Non standard stainless steel conveyor chains





Conveyor chains

Yuk reference	Pitch	Inner with	Roller diameter	Plates		Pins		Breaking load		Type
	P	B min	D2	width	thickness	diameter	length	Q min	Q max	
	mm	mm	mm	mm	mm	mm	mm	KN	KN	
70200LJ001*	20	16	12	16	3	8	33	23,1		A
70254LJ000	25,4	8	16	16	2	6	21	17,6		B
70350LJ000**	35	14	22	18	2,5	8	29	19,3		B
70350LJ003	35	16	14	18	2,5	8	31	19,3		A
70350LJ004	35	14	14	18	2,5	8	29	19,3		A
70350LJ005	35	16	20	18	2,5	8	29	19,3		B
70350LJ006	35	15	22	19,5	2,5	8	29	23,4		C
70413LJ000**	41,3	14	30	24	3	8	31	33		B
70413LJ002	41,3	10	16	22	3	9	27	33		A
70413LJ003	41,3	16	16	22	3	9	33	33		A
70414LJ001	41,4	22,23	17,8	20	3,4/2,7	8,22	39,3	33		A
70500LJ002	50	15	30	25	4	10	36	48,4		B
70500LJ003	50	12	25	20	3	7,9	28	29,7		B
70600LJ000	60	14	30	25	3	8	31	33		B
70600LJ001	60	14	32	25	3	8	31	33		B
70630LJ000**	63	16	25	19	3	8	33	26,4		B

* Fixed bush chain ** Available with POM roller

CONVEYOR LÁNCOK

Non standard stainless steel conveyor chains




Conveyor chains with attachments

Yuk reference	Pitch		Inner width	Roller diameter	Plates		Pins		Attachments						Breaking load																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																					
	P	B min			D2	H	T	D	L max	G	H4	F/2	N° Holes	D4		Pitches between attachments	Q min																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																			
			mm	mm											mm			mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm

* Available with POM roller

Non standard stainless steel conveyor chains




Conveyor chains with extended pins

Yuk reference	Pitch		Inner width	Roller	Plates		Pins		Extended pin		Breaking load		Type
	P	B min			Width	Thick-ness	Diameter	Length	Diameter	Length	Q min		
	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	KN		
70350PI000	35	18	20	18	2,5	8	31	10	30	19,3	C/2		
70350PI002	35	16	20	18	2,5	8	-	10	30	19,3	T/P		
70350PI003	35	10	20	18	2,5	8	26	10	30	19,3	C/2		
70413PI000	41,3	10	25	22	3	9	27	12	30	33	C/2		
70413PI001	41,3	16	16	22	3	9	33	12	40	33	C/2		
70500PI000	50	12	15	15	2,5	7	-	10	40	13,8	T/P		
70750PI000	75	11	25	20	3	8	-	12	30	29,7	T/P		


T/P - Extended pin on every pitches
C/2 - Extended pin on every 2 pitches
For other measures, please consult

TALPAS LÁNCOK, LÁNCVEZETŐK

Flat top chains



Stainless steel Flat top chains





Straight type

Reference	ISO	Pitch	Slot width		Hinge width		Working load		Breaking load		Weight per meter
		P	B		C		AISI 430	AISI 304	AISI 430	AISI 304	q
		mm	mm		mm		ΔdaN	ΔdaN	ΔdaN	ΔdaN	Kg/m
515		25,4	63,5	42							2,40
515		25,4	75,0	42		200	250		600	1000	2,72
515		25,4	82,5	42							2,95
812 / 815		38,1	31,75	22		80	100		240	400	1,10
812 / 815		38,1	44,45	22		80	100		240	400	1,38
812 / 815		38,1	63,5	42							2,10
812 / 815	C12S	38,1	76,2	42							2,30
812 / 815	C13S	38,1	82,5	42							2,40
812 / 815	C14S	38,1	88,9	42							2,50
812 / 815	C16S	38,1	101,6	42		200	250		600	1000	3,00
812 / 815	C18S	38,1	114,3	42							3,03
812 / 815	C24S	38,1	152,4	42							4,00
812 / 815	C30S	38,1	190,5	42							4,05
802 / 805	C30D	38,1	190,5	80		360	450		110	1800	5,55

It is possible produce these chains in other materials and different slot width

TALPAS LÁNCOK, LÁNCVEZETŐK

Stainless steel
Flat top chains




Side bow type

Reference	Pitch	Slat width	Width	Width	Height	Side bow radius min.	**Working load	Breaking load	Weight per meter
	P mm	B mm	C mm	D mm	E mm	mm	AdaN	AdaN	q Kg/m
88103-A	38,1	82,5	42,9		11,2	457			2,65
88103-B/TAB	38,1	82,5	42,9	56,2	18,6	457			3,15
88103MAG	38,1	82,5	42			457			2,50
88104-A	38,1	114,3	42,9		11,2	610			3,60
88104-B/TAB	38,1	114,3	42,9	56,2	18,6	610			3,90
88104MAG	38,1	114,3	42			610			3,25
88107-A	38,1	190,5	42,9		11,2	610			5,40
88107-B/TAB	38,1	190,5	42,9	56,2	18,6	610			5,70
88107MAG	38,1	190,5	42			610			5,05


MAG type chains are manufactured with magnetic stainless steel. The curved guides are magnetized on top to pull the chain to the seat and prevent it can get out of guide.

Thermoplastic
flat top chains



Straight type

Reference	Material	Pitch	Slat width	Hinge width	Pin diameter	Slat thickness	Weight per meter
		P mm	B mm	C mm	E mm	S mm	q Kg/m
LF820-82,5	Low friction acetal	38,1	82,5	42	6,35	4	0,87
LF820-101,6		38,1	101,6	42	6,35	4	0,90
LF820-114,3		38,1	114,3	42	6,35	4	0,98
LF820-152,4		38,1	152,4	42	6,35	4	1,22
LF820-190,5		38,1	190,5	42	6,35	4	1,33
LF821-190,5		38,1	190,5	136,5	6,35	5	2,5




Side bow type


Reference	Material	Pitch	Slat Width	Hinge Width	Pin diameter	Side bow radius min.	Guide width min	Slat thickness	Weight p meter
		P mm	B mm	C mm	E mm	R mm	mm	S mm	q Kg/m
880 series									
LF-82,5	Low friction acetal	38,1	82,5	42	6,35	500	44	4	1,07
LF-114,3		38,1	114,3	42	6,35	600	44	4	1,25
882 series									
LF-190,5	Low friction acetal	38,1	190,5	57,2	8,35	610	58	5	2,43

TALPAS LÁNCOK, LÁNCVEZETŐK


Roller chains guides




Reference	ISO	Pitch	W	H	A	h	Kg/m
YS-1	06B1	3/8"	15	10	5,4	1,5	0,135
YS-2	08B1	1/2"	20	10	7,4	2,2	0,185
YS-3	10B1	5/8"	20	10	9,2	2,6	0,160
YS-315	10B1	5/8"	20	15	9,2	2,6	0,260
YS-4	12B1	3/4"	25	10	11,3	2,4	0,210
YS-415	12B1	3/4"	25	15	11,3	2,4	0,325
YS-5	16B1	1"	40	15	16,5	3,5	0,470
YS-520	16B1	1"	40	20	16,5	3,5	0,660
YS-6	20B1	1 1/4"	45	15	19	4,3	0,530
YS-620	20B1	1 1/4"	45	20	19	4,3	0,720
YS-7	24B1	1 1/2"	60	15	24,5	5,6	0,786
YS-8	28B1	1 3/4"	75	20	30	6,9	1,130
YS-9	32B1	2"	86	20	30	7,8	1,210




Reference	ISO	Pitch	W	H	A	h	B	Kg/m
YD-1	06B2	3/8"	25	10	5,4	1,5	16	0,230
YD-2	08B2	1/2"	35	10	7,4	2,2	21	0,306
YD-3	10B2	5/8"	40	10	9,2	2,6	26	0,344
YD-315	10B2	5/8"	40	15	9,2	2,6	26	0,524
YD-4	12B2	3/4"	45	10	11,3	2,4	31	0,396
YD-415	12B2	3/4"	45	15	11,3	2,4	31	0,596
YD-5	16B2	1"	65	15	16,5	3,5	48	0,863
YD-520	16B2	1"	65	20	16,5	3,5	48	1,156
YD-6	20B2	1 1/4"	70	15	19	4,3	54,5	0,912
YD-620	20B2	1 1/4"	70	20	19	4,3	54,5	1,232
YD-7	24B2	1 1/2"	88	20	24,5	5,6	72	1,499
YD-8	28B2	1 3/4"	105	20	30	6,9	89	1,790
YD-9	32B2	2"	105	20	30	7,8	89	1,750



Reference	ISO	Pitch	W	H	A	h	B	Kg/m
YT-1	06B3	3/8"	35	10	5,4	1,5	25,9	0,306
YT-2	08B3	1/2"	45	10	7,4	2,2	35,3	0,381
YT-2-15	08B3	1/2"	45	15	7,4	2,2	35,3	0,595
YT-2-20	08B3	1/2"	45	20	7,4	2,2	35,3	0,808
YT-3	10B3	5/8"	55	10	9,2	2,6	42,5	0,455
YT-4	12B3	3/4"	65	10	11,3	2,4	50,3	0,548
YT-5	16B3	1"	85	15	16,5	3,5	80,3	1,187
YT-6	20B3	1 1/4"	92	15	19,0	4,3	92,0	1,304
YT-7	24B3	1 1/2"	121	20	24,5	5,6	121,5	2,247
YT-8	28B3	1 3/4"	149	25	30,0	6,9	149,3	3,622
YT-9	32B3	2"	149	30	30,0	7,8	149,3	4,282




Reference	ISO	Pitch	W	H	C	h	J	d	Kg/m
YU-1	06B	3/8"	20	15	9,2	4,2	2,8	4	0,257
YU-2	08B	1/2"	25	15	12,7	4,8	3,5	5	0,308
YU-3	10B	5/8"	25	15	15,2	5,1	3,6	6	0,296
YU-4	12B	3/4"	25	20	16,7	5,7	3,9	7	0,403
YU-5	16B	1"	35	25	24,4	10	8,4	9	0,624




Reference	ISO	Pitch	W	H	K	h	J	d	Profile	Kg/m
YUCG-1	06B	3/8"	20	10	15	4,2	2,8	4	C2010	0,720
YUCG-2	08B	1/2"	25	15	22	4,8	3,5	5	C2812	1,140
YUCG-3	10B	5/8"	25	15	22	5,1	3,6	6	C2812	1,130
YUCG-4	12B	3/4"	25	20	27	5,7	3,9	7	C2812	1,270
YUCG-5	16B	1"	35	25	33	10	8,4	9	C3818	2,030


Roller chains guides




Reference	ISO	Pitch	W	H1	H2	A	K	Profile	Kg/m
Y2PCG-1	06B1	3/8"	20	30	15,5	17,3	27	C2010	0,900
Y2PCG-2	08B1	1/2"	20	34	18	16,5	30	C2010	0,980
Y2PCG-3	10B1	5/8"	20	41	19,5	15,5	36	C2010	1,120
Y2PCG-4	12B1	3/4"	28	46,5	23	22,3	41	C2812	1,700
Y2PCG-5	16B1	1"	38	62	31	29,5	54	C3818	3,100



Reference	ISO	Pitch	W	H	K	h	A	Profile	Kg/m
YTCG-1	06B1	3/8"	20	15	17	1,5	5,4	C2010	0,620
YTCG-2	08B1	1/2"	20	15	17	2,2	7,4	C2010	0,695
YTCG-3	10B1	5/8"	20	15	17	2,6	9,2	C2010	0,700
YTCG-4	12B1	3/4"	20	15	18	2,4	11,3	C2010	1,170
YTCG-5	16B1	1"	28	15	18	3,5	16,5	C2812	2,246
YTCG-6	20B1	1 1/4"	38	25	30	4,3	19,0	C3818	2,306
YTCG-7	24B1	1 1/2"	38	25	30	5,6	24,6	C3818	2,590
YTCG-8	28B1	1 3/4"	38	25	30	6,9	30	C3818	2,410
YTCG-9	32B1	2"	38	25	30	7,8	30	C3818	2,480




Reference	ISO	Pitch	W	H	L	h	A	S	Kg/m
YUC-1	06B1	3/8"	25	10	15	1,5	5,4	4,4	0,170
YUC-2	08B1	1/2"	30	15	20	2,2	7,4	7,2	0,275
YUC-3	10B1	5/8"	33	20	23	2,6	9,2	9,5	0,405
YUC-4	12B1	3/4"	38	20	28	2,4	11,3	11,1	0,410
YUC-5	16B1	1"	51	25	41	3,5	16,5	16,5	0,510




Reference	ISO	Pitch	W	H	L	h	A	S	Kg/m
YUCD-1	06B2	3/8"	36	15	26	1,5	5,4	4,4	0,390
YUCD-2	08B2	1/2"	45	20	35	2,2	7,4	7,2	0,620
YUCD-3	10B2	5/8"	50	25	40	2,6	9,2	9,5	0,816
YUCD-4	12B2	3/4"	58	25	46	2,4	11,3	11,1	0,810
YUCD-5	16B2	1"	65	30	75	3,5	16,5	16,5	1,200

TALPAS LÁNCOK, LÁNCVEZETŐK


Roller chains guides




Reference	ISO	Pitch	W	H	K	L	h	A	S	Profile	Kg/m
YUCCG-1	06B1	3/8"	25	15	16	15	1,5	5,4	4,4	C2010	0,780
YUCCG-2	08B1	1/2"	30	25	27	20	2,2	7,4	7,2	C2812	1,100
YUCCG-3	10B1	5/8"	35	30	32	23	2,6	9,2	9,5	C2812	1,305
YUCCG-4	12B1	3/4"	38	35	38	28	2,4	11,3	11,1	C3818	2,335
YUCCG-5	16B1	1"	51	40	45	41	3,5	16,5	16,5	C3818	2,440



Reference	ISO	Pitch	W	H	K	h	A	Profile	Kg/m
YTCGD-1	06B2	3/8"	15,5	10	15	1,5	5,4	C2010	0,615
YTCGD-2	08B2	1/2"	21,5	10	17	2,2	7,4	C2010	0,715
YTCGD-3	10B2	5/8"	26	15	17	2,6	9,2	C2812	1,165
YTCGD-4	12B2	3/4"	30,7	15	18	2,4	11,3	C2812	1,200




Reference	ISO	Pitch	W	H	C	h	L	d	J	D	Kg/m
YGH-1	06B	3/8"	20	25	9,3	10	5,6	4	8,7	6,6	0,414
YGH-2	08B	1/2"	24	30	12,6	12,7	7,6	5	11,5	8,7	0,564
YGH-3	10B	5/8"	30	35	15,4	14,8	9,5	6	13,5	10,4	0,832
YGH-4	12B	3/4"	40	35	16,9	17,5	11,5	7	15,9	12,3	1,106
YGH-5	16B	1"	40	45	24,4	26,8	16,9	9	25,7	16,1	1,231
YGH-6	20B	1 1/4"	50	50	27,5	31,2	19,4	11	29,5	19,3	1,726
YGH-7	24B	1 1/2"	60	60	36,5	40,1	25,2	16	38,2	25,7	2,332
YGH-8	28B	1 3/4"	70	70	41,5	48,9	30,8	17	46,9	28,3	3,173
YGH-9	32B	2"	75	75	44,5	53,0	30,8	19	47,3	29,6	3,264



Reference	ISO	Pitch	W	K	L	D	Profile	Kg/m
YGHCG-1	06B	3/8"	30	24	5,6	6,6	C3024	2,150
YGHCG-2	08B	1/2"	30	24	7,6	8,7	C3024	2,150
YGHCG-3	10B	5/8"	30	24	9,5	10,4	C3024	2,100
YGHCG-4	12B	3/4"	30	24	11,5	12,3	C3024	2,060
YGHCG-5	16B	1"	45	40	16,9	16,1	C4540	2,060


Stainless steel profile can be provided.
Standard length 2 meters.

Roller chains guides




Reference	ISO	Pitch	W	H	K	L	J	h	d	D	C	Profile	Kg/m
YGHLOG-1	06B	3/8"	20	17,5	21	5,6	8,7	9,9	4	8,6	9,3	C2010	0,622
YGHLOG-2	08B	1/2"	28	27,5	32	7,6	11,5	12,7	5	8,7	12,6	C2812	1,450
YGHLOG-3	10B	5/8"	28	27,5	32	9,5	13,5	14,8	6	10,4	15,4	C2812	1,402
YGHLOG-4	12B	3/4"	38	34,0	43	11,5	15,9	17,5	7	12,3	16,9	C3818	1,709
YGHLOG-5	16B	1"	38	40	50	16,9	25,7	26,8	9	16,1	24,4	C3818	1,800
YGHLOG-6	20B	1 1/4"	60	45	55	19,4	29,5	31,2	11	19,3	27,5	C6020	4,800
YGHLOG-7	24B	1 1/2"	60	55	65	25,2	38,2	40,1	16	25,7	36,5	C6020	5,000
YGHLOG-8	28B	1 3/4"	70	70	80	30,8	46,9	48,9	17	28,3	41,5	C6020	6,200
YGHLOG-9	32B	2"	70	70	80	30,8	47,3	53,0	19	28,6	44,5	C6020	6,200

Metal profile C-15



Reference	ISO	Pitch	K	W	L	I	J	h	d	D	Kg/m
YGHPCG-1	06B	3/8"	25	31	53	5,6	8,7	9,9	4	6,6	2,340
YGHPCG-2	08B	1/2"	25	31	53	7,6	11,5	12,7	5	8,7	2,300
YGHPCG-3	10B	5/8"	25	31	53	9,5	13,5	14,8	6	10,4	2,250
YGHPCG-4	12B	3/4"	25	31	53	11,5	15,9	17,5	7	12,3	2,250


Metal profile C-14




Reference	ISO	Pitch	K	W	L	I	J	h	d	D	Kg/m
YGHCCG-1	06B	3/8"	25	31	47	5,6	8,7	9,9	4	6,6	2,150
YGHCCG-2	08B	1/2"	25	31	47	7,6	11,5	12,7	5	8,7	2,150
YGHCCG-3	10B	5/8"	25	31	47	9,5	13,5	14,8	6	10,4	2,100
YGHCCG-4	12B	3/4"	25	31	47	11,5	15,9	17,5	7	12,3	2,060

TALPAS LÁNCOK, LÁNCVEZETŐK


Belts guides




Reference	W	H	h	A	Kg/m
YCT 10Z	20	10	3	6,5	0,197
YCT 13A	20	12	5	8	0,232
YCT 15E	25	12	5	10	0,292
YCT 17B	30	15	8	10,5	0,429
YCT 22C	35	20	11	13,5	0,660
YCT 30D	40	25	13	19	0,944



Reference	D	W	H	h	Kg/m
YCOR-04	4	15	10	2	0,144
YCOR-05	5	15	10	2,5	0,140
YCOR-06	6	20	10	3	0,186
YCOR-08	8	20	10	4	0,175
YCOR-10	10	25	12	5	0,260
YCOR-12	12	25	12	6	0,244
YCOR-15	15	25	15	7,5	0,285
YCOR-20	20	30	20	10	0,442




Reference	W	K	H	h	Profile	Kg/m
YHOG-2005	20	6	5	0,8	C2405	0,250
YHOG-2010	20	14	10	4	C2010	0,790
YHOG-2015	20	17	15	7	C2010	0,880
YHOG-2020	20	22	20	12	C2010	0,940
YHOG-2810	28	15	10	3	C2812	1,160
YHOG-2815	28	18	15	5	C2812	1,320
YHOG-2820	28	24	20	12	C2812	1,480
YHOG-3812	38	22	12	4	C3818	2,200
YHOG-3815	38	24	15	6	C3818	2,460
YHOG-3820	38	30	20	12	C3818	2,680
YHOG-6020	60	30	20	10	O6020	3,260




Reference	W	H	h	K	A	Profile	Kg/m
YCTCG 10Z	20	15	3	17	6,5	C2010	0,787
YCTCG 13A	20	15	5	17	8	C2010	0,787
YCTCG 15E	25	20	5	24	10	C2812	1,352
YCTCG 17B	30	20	8	24	10,5	C2812	1,439
YCTCG 22C	38	25	11	32	13,5	C3818	2,285
YCTCG 30D	40	30	13	35	19	C3818	2,574

Belts guides





Reference	D	W	H	h	K	Profile	Kg/m
YCOROG 04	4	20	10	2	14	C2010	0,660
YCOROG 05	5	20	10	2,5	14	C2010	0,675
YCOROG 06	6	20	10	3	14	C2010	0,690
YCOROG 08	8	20	10	4	14	C2010	0,690
YCOROG 10	10	28	15	5	18	C2812	1,179
YCOROG 12	12	28	15	6	18	C2812	1,140
YCOROG 15	15	28	15	7,5	18	C2812	1,160
YCOROG 20	20	28	20	10	24	C2812	1,260

YMC profile
2020 Type



Other guides for
plain belts*



* Indicate dimensions when placing offer / order
Stainless steel profile can be provided.
Standard length 2 meters.

TALPAS LÁNCOK, LÁNCVEZETŐK

Flat top chains guides

For chain 881 TAB
880 TAB

Slat width 82,5 mm

R1	R2	R3	R4	P	AG
500	-	-	-	-	100
500	590	-	-	90	190
500	590	680	-	90	280
500	590	680	770	90	370
650	-	-	-	-	100
650	740	-	-	90	190
650	740	830	-	90	280
650	740	830	920	90	370
800	-	-	-	-	100
800	950	-	-	90	190
800	950	1040	-	90	280
800	950	1040	1130	90	370





Slat width 114,3 mm

550	-	-	-	-	130
550	875	-	-	125	255
550	875	800	-	125	380
550	875	800	1025	125	505
650	-	-	-	-	130
650	775	-	-	125	255
650	775	900	-	125	380
650	775	900	1025	125	505

Other dimensions upon request



Straight guide upon request




Flat top chains guides


For chain 882 TAB

Slat width	Radius min.	Pitch P	AG
190,5	610	-	200
190,5	610	198	398
254	610	-	270
254	610	290	530
304,8	610	-	320
304,8	610	310	630


1 set = round way.
Other dimensions can be
manufactured upon request



A	Chain
100	K3 ^{1/2} "
130	K4 ^{1/2} "
210	K7 ^{1/2} "



A	Chain
100	K3 ^{1/2} "
130	K4 ^{1/2} "
210	K7 ^{1/2} "
270	K10"
320	K12"




A	Chain
100	K3 ^{1/2} "
130	K4 ^{1/2} "
210	K7 ^{1/2} "
270	K10"
320	K12"




TALPAS LÁNCOK, LÁNCVEZETŐK


Special guides/profiles




Z profile - green




L profile - green



T profile - green




C profile for plates - green




U-41 profile - black




U-45 profile - black




P profile 25 - green




P profile 40 - green



P profile 20 - green



DZ profile - green



SH profile - Black



H profile - Black

To fit on bar Ø10 mm or 3/8"



Round profile Ø 10 - white

To fit on bar Ø12 mm or 1/2"




Round profile Ø 12 - white

Dimensions upon request




Rectangular



Metal profiles



Profile C-14



Profile C-15



Holes on flange C-14 y C-15

Galvanized	Stainless steel	B	H	b	d	Kg/m
24 X 5,2	24 X 5,2	24	5,2	17,5	1,0	0,280
20 X 10	20 X 10	20	10	10	1,3	0,430
28 X 12	28 X 12	28	12	14	2,2	0,950
28 X 16	28 X 16	28	16	14	2,3	1,150
36 X 18	36 X 18	36	18	22	1,5	0,980
30 X 24	30 X 24	30	24	20	1,5	0,940
36 X 18	36 X 18	36	18	22	2,5	1,430
45 X 40	45 X 40	45	40	31	2,0	2,050
60 X 20	60 X 20	60	20	36	2,5	2,160
C-14	C-14	31	25	20	2,0	1,200
C-15	C-15	31	25	20	2,0	1,200

Polyethylene sheets

Dimensions	Color	Qualities available
1 X 1000 X 2000	NAT/V/N	PE-500 V / PE-1000 V
2 X 1000 X 2000	NAT/V/N	PE-500 V / PE-1000 V
3 X 1000 X 2000	NAT/V/N	PE-500 V / PE-1000 V
4 X 1000 X 2000	NAT/V/N	PE-500 V / PE-1000 V
5 X 1000 X 2000	NAT/V/N	PE-500 V / PE-1000 V
6 X 1000 X 2000	NAT/V/N	PE-500 V / PE-1000 V
8 X 1000 X 2000	NAT/V/N	PE-500 V / PE-1000 V
10 X 1000 X 2000	NAT/V/N	PE-500 V / PE-1000 V
12 X 1000 X 2000	NAT/V/N	PE-500 V / PE-1000 V
15 X 1000 X 2000	NAT/V/N	PE-500 V / PE-1000 V
20 X 1000 X 2000	NAT/V/N	PE-500 V / PE-1000 V
21 X 1000 X 2000	NAT/V/N	PE-500 V / PE-1000 V
23 X 1000 X 2000	NAT/V/N	PE-500 V / PE-1000 V
25 X 1000 X 2000	NAT/V/N	PE-500 V / PE-1000 V
30 X 1000 X 2000	NAT/V/N	PE-500 V / PE-1000 V
36 X 1000 X 2000	NAT/V/N	PE-500 V / PE-1000 V
40 X 1000 X 2000	NAT/V/N	PE-500 V / PE-1000 V
45 X 1000 X 2000	NAT/V/N	PE-500 V / PE-1000 V
50 X 1000 X 2000	NAT/V/N	PE-500 V / PE-1000 V
55 X 1000 X 2000	NAT/V/N	PE-500 V / PE-1000 V
60 X 1000 X 2000	NAT/V/N	PE-500 V / PE-1000 V
70 X 1000 X 2000	NAT/V/N	PE-500 V / PE-1000 V
80 X 1000 X 2000	NAT/V/N	PE-500 V / PE-1000 V

Nat.= Natural V= Green N=Black
Other dimensions upon request

Tanúsítvány

Szabvány **ISO 14001:2015**

Tanúsítvány jegyzéksz. **01 104 1724130**

Tanúsítvány birtokosa: **ADIX-TRADE Kereskedelmi
és Szolgáltató Kft.**
Nyíl u. 73-79
4028 Debrecen
Magyarország

A mellékletben felsorolt telephelyekkel együtt.

Alkalmazási terület: csapágy, karbantartó anyagok és munkavédelmi termékek
kereskedelme.

A tanúsítási audit során bizonyítást nyert, hogy a rendszer
megfelel az ISO 14001:2015 követelményeinek.

Érvényesség: A tanúsítvány érvényes 2020.12.15-től 2023.06.20-ig.

2020.12.15.

Manuela Haid

TÜV Rheinland Cert GmbH
Am Grauen Stein - 51105 Köln

www.tuv.com



TÜVRheinland®
Precisely Right.

Tanúsítvány

Szabvány **ISO 9001:2015**

Tanúsítvány jegyzéksz. **01 100 1724130**

Tanúsítvány birtokosa: **ADIX-TRADE Kereskedelmi
és Szolgáltató Kft.**
Nyíl u. 73-79
4028 Debrecen
Magyarország

A mellékletben felsorolt telephelyekkel együtt.

Alkalmazási terület: csapágy, karbantartó anyagok és munkavédelmi termékek
kereskedelme.

A tanúsítási audit során bizonyítást nyert, hogy a rendszer
megfelel az ISO 9001:2015 követelményeinek.

Érvényesség: A tanúsítvány érvényes 2020.12.15-től 2023.06.20-ig.

2020.12.15.

Manuela Haid

TÜV Rheinland Cert GmbH
Am Grauen Stein - 51105 Köln

www.tuv.com



TÜVRheinland®
Precisely Right.



ADIX

Adix láncszakértő: Farkas Zoltán
+36 20 342 5897 • farkas.zoltan@adix.hu • adix@adix.hu
www.adix.hu • www.specialislanc.hu